



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
CONTROLLER	RideControl One Ant+
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak 400Wh
FRAME	
SIZES	S, M, L
COLORS	Black
FRAME	ALUXX Aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
FORK	SR Suntour NEX E25 63mm travel
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Connect Riser S:31.8x620mm, M:31.8x680mm, L:31.8x680mm
GRIPS	Giant Connect Ergo
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Giant Sport Comfort
PEDALS	PP Pedal
DRIVETRAIN	
SHIFTERS	Shimano Altus
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Alivio, 9-speed
BRAKES	Tektro HD-M275, hydraulic disc, 160/180mm
BRAKE LEVERS	Tektro HD-M275
CASSETTE	Shimano CS-HG200, 11-36T, 9-speed
CHAIN	KMC e.9 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 42T
BOTTOM BRACKET	-

WHEELS	
RIMS	Giant GX03V, 622x21mm Aluminium
HUBS	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
SPOKES	Stainless steel
TIRES	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready W/O Reflex (GU: w/reflex)

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	435	485	535
Seat Tube Angle	73,0°	73,0°	73,0°
Top Tube Length (mm)	570	590	610
Head Tube Length (mm)	130	140	155
Head Tube Angle	69,5°	69,5°	69,5°
Fork Rake (mm)	42	42	42
Trail (mm)	91,3	91,3	91,3
Wheelbase (mm)	1112	1121	1142
Chain Stay Length (mm)	455	455	455
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	609	618	633
Reach (mm)	383	401	416
Stand Over Height (mm)	682	676	665
Handlebar Width (mm)	640	680	680
Stem Length (mm)	60	70	80
Crank Length (mm)	170	170	170
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.