

# 디파이 어드밴스 SL 0

**GIANT**



## 스펙

프레임	
사이즈	XS, S, M, M/L
색상	Blue Dragonfly/Black/Chrome
프레임	Advanced SL-grade composite, disc
포크	Advanced SL-grade composite, full-composite OverDrive Aero steerer, disc
서스펜션	N/A
부품	
핸들바	Giant Contact SLR D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm
GRIPS	Stratus Lite 3.0
스템	Giant Contact SLR Aero Light XS:80mm, S:90mm, M:100mm, M/L:100mm
시트스트	Giant D-Fuse SLR, composite, -5/+15mm offset
안장	Giant Fleet SLR
페달	N/A
구동계	
변속기	SRAM RED eTap AXS
앞 변속기	SRAM RED eTap AXS
뒷 변속기	SRAM RED eTap AXS
브레이크	SRAM RED eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]160mm
브레이크 레버	SRAM RED eTap AXS hydraulic
스프라켓	SRAM Force, 12-speed, 10x36
체인	SRAM RED D1
크랭크 셋	SRAM RED D1 DUB, 33/46 with Quarq DZero power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm
BB	SRAM DUB, press fit

바퀴	
휠	CADEX 36 Disc WheelSystem, [F]36mm, [R]36mm
허브	[F] CADEX R1 Hub, CenterLock, 12mm thru-axle [R] CADEX R1-C30 Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
스포크	CADEX Aero Carbon Spoke
타이어	CADEX Classic, tubeless, 700x32c (33.5mm), folding
추가 기능	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size

가격: ₩14,000,000

## 지오메트리

프레임	XS	S	M	ML
시트 튜브 길이 (mm)	410	445	480	515
시트 튜브 각도	74.5°	74.0°	73.5°	73.0°
탑튜브 길이 (mm)	515	530	545	560
헤드 튜브 길이 (mm)	125	135	150	175
헤드튜브 각도	70.5°	71.8°	72.5°	72.5°
포크 레이크 (mm)	50	50	50	50
트레일 (mm)	71.6	63.4	58.6	58.6
휠베이스 (mm)	995	994	998	1010
체인스테이 길이 (mm)	420	420	420	420
BB (mm)	75	75	75	70
스택 (mm)	527	541	558	577
범위 (mm)	369	375	380	384
스탠드 오버 (mm)	705	733	762	796
핸들바 폭 (mm)	400	400	420	420
스템 길이 (mm)	80	90	100	100
크랭크 길이 (mm)	170	170	172.5	172.5
휠사이즈	700C	700C	700C	700C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.