

# 프로펠 어드밴스 SL 0 RED

GIANT



## 스펙

프레임	
사이즈	XS, S, M, M/L
색상	Arctic Light/Chrome
프레임	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
포크	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
서스펜션	N/A
부품	
핸들바	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
스텝	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
시트포스트	Advanced SL-grade composite, integrated design, -5/+15mm offset
안장	CADEX AMP
구동계	
변속기	SRAM RED AXS HRD, ED-RED-E1
앞 변속기	SRAM RED AXS FD-RED-E-E1
뒷 변속기	SRAM RED AXS RD-RED-E-E1
브레이크	SRAM RED hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
브레이크 레버	SRAM RED AXS HRD, ED-RED-E1
스프라켓	SRAM RED, 12-speed, 10x33
체인	SRAM RED CN-RED-E1
크랭크 셋	SRAM RED PM E1 DUB, 37/50 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BB	SRAM DUB ceramic, press fit

바퀴	
휠	CADEX Ultra 50 WheelSystem, [F]50mm, [R]50mm
허브	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
스포크	CADEX Super Aero Carbon Spoke
타이어	CADEX Aero, tubeless, 700x25c (26.5mm), folding
추가 기능	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
최대 타이어 클리어런스	32mm

가격: ₩13,400,000

## 지오메트리

프레임	XS	S	M	ML
시트 튜브 길이 (mm)	680	710	740	770
시트 튜브 각도	74.5°	74.0°	73.5°	73.0°
탑튜브 길이 (mm)	520	535	550	565
헤드 튜브 길이 (mm)	120	130	145	165
헤드튜브 각도	71.0°	72.3°	73.0°	73.0°
포크 레이크 (mm)	45	45	45	45
트레일 (mm)	70.5	62.5	57.8	57.8
휠베이스 (mm)	976	977	980	991
체인스테이 길이 (mm)	405	405	405	405
BB (mm)	72	70	70	67
스택 (mm)	517	528	545	562
범위 (mm)	376	383	388	393
스탠드 오버 (mm)	734	755	775	794
핸들바 폭 (mm)	380	380	400	400
스텝 길이 (mm)	80	90	100	110
크랭크 길이 (mm)	165	165	170	170

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.