

앤섬 어드밴스 SL 1

GIANT



스펙

프레임	
사이즈	S, M
색상	Rainbow Black/Rainbow Charcoal
프레임	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
포크	RockShox Sid Select+ 3P, 120mm, Charger Race Day 2 damper, Boost 15x110, 44mm offset, remote lockout
서스펜션	RockShox SidLuxe Select+, RL damper, Solo Air, 210/50, TwistLoc Ultimate
부품	
핸들바	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	SRAM TwistLoc Ultimate
스텝	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
시프스트	Giant Contact Switch SL dropper, remote S: 110mm travel / 30.9 x 395mm M: 140mm travel / 30.9 x 395mm L: 140mm travel
안장	Giant Grit SL
페달	N/A
구동계	
변속기	SRAM AXS Pod, discrete clamp, 1x12
앞 변속기	N/A
뒷 변속기	SRAM GX AXS Transmission
브레이크	Shimano Deore XT BR-M8220, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
브레이크 레버	Shimano Deore XT BL-M8200
스프라켓	SRAM XS 1275, 10x52
체인	SRAM GX Transmission
크랭크 셋	SRAM GX Transmission, 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BB	SRAM DUB, press fit

바퀴	
휠	Giant XCR WheelSystem
허브	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
스포크	Carbon
타이어	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
추가 기능	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

가격: ₩9,590,000

지오메트리

프레임	S		M	
	LOW	HIGH	LOW	HIGH
시트 튜브 길이 (mm)	400		420	
시트 튜브 각도	75.5°	76.0°	75.5°	76.0°
탑튜브 길이 (mm)	576	574	602	600
헤드 튜브 길이 (mm)	90		95	
헤드 튜브 각도	66.5°	67.0°	66.5°	67.0°
포크 레이크 (mm)	44		44	
트레일 (mm)	116	112.2	115.9	112.2
휠베이스 (mm)	1141	1140	1168	1167
체인스테이 길이 (mm)	437	435	437	435
BB (mm)	51	45	51	45
스택 (mm)	602	599	607	603
범위 (mm)	420	425	445	450
스탠드 오버 (mm)	769	775	764	771
핸들바 폭 (mm)	780		780	
스텝 길이 (mm)	60		70	
크랭크 길이 (mm)	170		170	

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.