

# 리볼트 어드밴스 SL 1



## 스펙

| 프레임     |                                                                                                                  |
|---------|------------------------------------------------------------------------------------------------------------------|
| 사이즈     | XS, S, M, M/L, L, XL                                                                                             |
| 색상      | Tempest Purple                                                                                                   |
| 프레임     | Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout                                               |
| 포크      | Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc                     |
| 부품      |                                                                                                                  |
| 핸들바     | Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm |
| GRIPS   | Stratus Lite 3.0                                                                                                 |
| 스텝      | Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110                                      |
| 시트포스트   | Giant Contact SLR XR D-Fuse, composite, 20mm offset                                                              |
| 안장      | Giant Grit SLR                                                                                                   |
| 구동계     |                                                                                                                  |
| 변속기     | SRAM Force XPLR AXS E1, 1x13                                                                                     |
| 뒷 변속기   | SRAM Force XPLR AXS E1                                                                                           |
| 브레이크    | SRAM Force AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm                                           |
| 브레이크 레버 | SRAM Force E1 hydraulic                                                                                          |
| 스프라켓    | SRAM Force E1, 13-speed, 10x46                                                                                   |
| 체인      | SRAM Force E1                                                                                                    |
| 크랭크 셋   | SRAM Force XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm           |
| BB      | SRAM DUB, press fit                                                                                              |

| 바퀴           |                                                                                                                    |
|--------------|--------------------------------------------------------------------------------------------------------------------|
| 휠            | Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm                                                       |
| 허브           | [F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock |
| 스포크          | Aero Bladed Carbon Spoke                                                                                           |
| 타이어          | CADEX GXR, 700x45c, tubeless                                                                                       |
| 추가 기능        | tubeless prepared, computer mount, chain guide                                                                     |
| LIMITS       |                                                                                                                    |
| 최대 타이어 클리어런스 | 700x53mm                                                                                                           |
| 최대 체인링 사이즈   | 54t                                                                                                                |

가격: ₩9,990,000

## 지오메트리

| 프레임           | XS    | S     | M     | ML    |
|---------------|-------|-------|-------|-------|
| 시트 튜브 길이 (mm) | 430   | 450   | 470   | 490   |
| 시트 튜브 각도      | 75.0° | 74.5° | 74.5° | 74.0° |
| 탑튜브 길이 (mm)   | 530   | 540   | 550   | 565   |
| 헤드 튜브 길이 (mm) | 90    | 100   | 120   | 135   |
| 헤드튜브 각도       | 70.5° | 71.0° | 71.5° | 72.0° |
| 포크 레이크 (mm)   | 50    | 50    | 50    | 50    |
| 트레일 (mm)      | 78    | 74    | 71    | 67    |
| 휠베이스 (mm)     | 1026  | 1027  | 1033  | 1039  |
| 체인스테이 길이 (mm) | 433   | 433   | 433   | 433   |
| BB (mm)       | 80    | 80    | 80    | 80    |
| 스택 (mm)       | 525   | 536   | 557   | 573   |
| 범위 (mm)       | 389   | 391   | 395   | 401   |
| 스탠드 오버 (mm)   | 726   | 743   | 762   | 779   |
| 핸들바 폭 (mm)    | 380   | 380   | 400   | 400   |
| 스텝 길이 (mm)    | 70    | 80    | 90    | 100   |
| 크랭크 길이 (mm)   | 165   | 165   | 170   | 170   |
| 휠사이즈          | 700C  | 700C  | 700C  | 700C  |

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.