

STANCE 0



SPECS

FRAME	
SIZES	XS, S, M, L, XL
COLOURS	Moonstone
FRAME	ALUXX-grade aluminium front and rear triangles, UDH, 130mm FlexPoint suspension, 12x148mm thru-axle
FORK	Giant STL 34 RC, dual-air, 140mm, 15x110mm thru-axle
SHOCK	Crest, FloTrac Elite, 2 position lever, trunnion mount
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35, alloy, XS, S 20mm rise, M, L, XL 35mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Contact Ergo Trail
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
REAR DERAILLEUR	SRAM Eagle 90 Transmission
BRAKES	TRP EVO Comp, hydraulic, TRP 2.3mm rotors [F]180mm, [R]180mm
BRAKE LEVERS	TRP EVO Comp
CASSETTE	SRAM XS-1270 Transmission, 10x52
CHAIN	SRAM Eagle 70 Transmission
CRANKSET	SRAM Eagle 90 Transmission, 30t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, threaded

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy, 29", 30mm inner width
HUBS	[F] Giant Boost Alloy Hub, 6 Bolt, Sealed Bearing, 28H [R] Giant Boost Alloy Hub, 6 Bolt, Sealed Bearing, HG, 28H
SPOKES	Sapim Race
TYRES	[F] Maxxis Dissector 29x2.4WT, TLR, EXO, Tubeless [R, size S, M, L & XL] Maxxis Dissector 29x2.4 WT, TLR, EXO or [R, size XS] Maxxis Dissector 27.5x2.4 WT, TLR, EXO, tubeless
EXTRAS	Tubeless prepared
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	32t

Price: \$3,899.00

GEOMETRY

FRAME	XS	S	M	L	XL
Seat Tube Length (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Seat Tube Angle	77.0°	76.5°	76.5°	76.5°	76.5°
Top Tube Length (mm)	547	567	600	627	659
Head Tube Length (mm)	95	100	110	120	130
Head Tube Angle	65.0°	65.0°	65.0°	65.0°	65.0°
Fork Rake (mm)	44	44	44	44	44
Trail (mm)	129	129	129	129	129
Wheelbase (mm)	1158	1176	1210	1239	1274
Chain Stay Length (mm)	440	442	442	442	442
Bottom Bracket Drop (mm)	25	40	40	40	40
Stack (mm)	613	615	624	633	642
Reach (mm)	405	420	450	475	505
Stand Over Height (mm)	758	754	748	744	738
Stem Length (mm)	40	40	40	40	40
Crank Length (mm)	165	165	165	165	165
Wheel Size	29" [F] 27.5" [R]	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.