

STANCE 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L, XL
FARBE	Moonstone/Chrome
RAHMEN	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
GABEL	Giant STL 34 dual air, 140mm, 15x110, thru-axle
DÄMPFER	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
KOMPONENTEN	
LENKER	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
GRIFFE	Giant Tactal, lock on
VORBAU	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SATTEL	Giant Contact Ergo Trail
ANTRIEB	
SCHALTHEBEL	SRAM Eagle 90, 1x12
SCHALTWERK	SRAM Eagle 90 Transmission
BREMSEN	TRP EVO Comp HD-M7040, hydraulic, TRP-SO6E, 6-bolt rotors [F]180mm, [R]180mm
BREMSHEBEL	TRP EVO Comp
KASSETTE	SRAM XS 1270, 10x52
KETTE	SRAM 70 Transmission
KURBEL	SRAM 90 T-Type, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
TRETLAGER	SRAM DUB, threaded

LAUFRÄDER	
FELGEN	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NABE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
SPEICHEN	Sapim, 28, J-bend
REIFEN	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIEDATEN

RAHMEN	XS	S	M	L	XL
Sitzrohrlänge (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Sitzrohrwinkel	77.0°	76.5°	76.5°	76.5°	76.5°
Oberrohrlänge (mm)	547	567	600	627	659
Steuerrohr-Länge (mm)	95	100	110	120	130
Steuerrohr-Winkel	65.0°	65.0°	65.0°	65.0°	65.0°
Gabelneigung (mm)	44	44	44	44	44
Trail (mm)	129	129	129	129	129
Radstand (mm)	1158	1176	1210	1239	1274
Kettenstreben-Länge (mm)	440	442	442	442	442
Tretlager-Höhe (mm)	25	40	40	40	40
Stack (mm)	613	615	624	633	642
Reach (mm)	405	420	450	475	505
Überstandshöhe (mm)	758	754	748	744	738
Lenkerbreite (mm)	760	760	760	780	780
Vorbaulänge (mm)	40	40	40	40	40
Kurbellänge (mm)	165	165	165	165	165
Radgrösse	29" [F] 27.5" [R]	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.