

STANCE 0



TECHNIQUES

CADRE	
TAILLES	XS (mullet), S, M, L, XL (29")
COLORIS	Moonstone
CADRE	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
FOURCHE	Giant STL 34 dual air, 140mm, 15x110, thru-axle
AMORTISSEUR	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
COMPOSANTS	
CINTRE	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
POIGNÉES	Giant Tactal, lock on
POTENCE	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
TIGE DE SELLE	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Contact Ergo Trail
DÉRAILLEUR	
MANETTES	SRAM Eagle 90, 1x12
DÉRAILLEUR ARRIÈRE	SRAM Eagle 90 Transmission
FREINS	TRP EVO Comp HD-M7040, hydraulic, TRP-SO6E, 6-bolt rotors [F]180mm, [R]180mm
LEVIER DE FREIN	TRP EVO Comp
CASSETTE	SRAM XS 1270, 10x52
CHAÎNE	SRAM 70 Transmission
PÉDALIER	SRAM 90 T-Type, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
BOITIER DE PÉDALIER	SRAM DUB, threaded

ROUES	
JANTES	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MOYEUX	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
RAYONS	Sapim, 28, J-bend
PNEUS	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 2 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	L	XL
Longueur de tube de selle (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Angle de tube de selle	77,0°	76,5°	76,5°	76,5°	76,5°
Longueur du tube supérieur (mm)	547	567	600	627	659
Longueur du tube de direction (mm)	95	100	110	120	130
Angle du tube de direction	65,0°	65,0°	65,0°	65,0°	65,0°
Déport de fourche (mm)	44	44	44	44	44
Trail (mm)	129	129	129	129	129
Empattement (mm)	1158	1176	1210	1239	1274
Longueur des bases (mm)	440	442	442	442	442
Drop du boîtier de pédalier (mm)	25	40	40	40	40
Stack (mm)	613	615	624	633	642
Reach (mm)	405	420	450	475	505
Hauteur en statique (mm)	758	754	748	744	738
Largeur de cintre (mm)	760	760	760	780	780
Longueur de potence (mm)	40	40	40	40	40
Longueur des manivelles (mm)	165	165	165	165	165
Diamètre des roues	29" [F] 27.5" [R]	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.