

STANCE 0



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L, XL
BARVE	Moonstone/Chrome
OKVIR	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
VILICE	Giant STL 34 dual air, 140mm, 15x110, thru-axle
AMORTIZER	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
KOMPONENTE	
KRMILO	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
GRIPS	Giant Tactal, lock on
OPORA KRMILA	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
OPORA SEDEŽA	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDEŽ	Giant Contact Ergo Trail
POGON	
PRESTAVNE ROČICE	SRAM Eagle 90, 1x12
ZADNJI MENJALNIK	SRAM Eagle 90 Transmission
ZAVORE	TRP EVO Comp HD-M7040, hydraulic, TRP-SO6E, 6-bolt rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	TRP EVO Comp
VERIŽNIK	SRAM XS 1270, 10x52
VERIGA	SRAM 70 Transmission
GONILKE Z VERIŽNIKI	SRAM 90 T-Type, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, threaded

OBROČNIKI	
OBROČI	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
NAPERE	Sapim, 28, J-bend
PLAŠČI	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
DODATKI	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	XS	S	M	L	XL
Dolžina sedežne cevi (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Kot sedežne cevi	77,0°	76,5°	76,5°	76,5°	76,5°
Top Tube Length (mm)	547	567	600	627	659
Višina glave okvirja (mm)	95	100	110	120	130
Krmilni kot	65,0°	65,0°	65,0°	65,0°	65,0°
Zamik vpetja osi (mm)	44	44	44	44	44
Trail (mm)	129	129	129	129	129
Medosna razdalja (mm)	1158	1176	1210	1239	1274
Dolžina cevi ob verigi (mm)	440	442	442	442	442
Bottom Bracket Drop (mm)	25	40	40	40	40
Oddaljenost zgornje cevi od gonilne osi (mm)	613	615	624	633	642
Doseg (mm)	405	420	450	475	505
Višina zgornje cevi (mm)	758	754	748	744	738
Širina krmila (mm)	760	760	760	780	780
Dolžina opore krmila (mm)	40	40	40	40	40
Dolžina gonilke (mm)	165	165	165	165	165
Velikost obročnikov	29" [F] 27.5" [R]	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.