

STANCE 29 1

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Rosewood
FRAME	ALUXX-Grade Aluminum, 120mm FlexPoint suspension
FORK	Crest 34 SL RCL, 130mm, Boost 15x110 QR, custom tuned for Giant
SHOCK	RockShox Monarch R, 184.15/44.45, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 780x31.8mm
GRIPS	Giant Sole-O
STEM	Giant Contact S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Giant Contact Switch dropper, remote S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL: 150mm travel / 30.9 x 440mm
SADDLE	Giant Romero
PEDALS	platform [GC,GT]
DRIVETRAIN	
SHIFTERS	SRAM SX Eagle, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM SX Eagle
BRAKES	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	SRAM SX Eagle, 11x50
CHAIN	SRAM SX Eagle
CRANKSET	SRAM SX Eagle DUB, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant AM 29 alloy, tubeless ready
HUBS	[F] Giant Tracker Performance Boost 15x110, sealed bearing [R] Giant Tracker Giant Sport QR141, loose ball
SPOKES	Sapim
TIRES	Maxxis Forecaster 29x2.35, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.4", max chainring size 32t

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	380	431	482	507
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	570	593	624	645
Head Tube Length (mm)	100	100	125	140
Head Tube Angle	67,5°	67,5°	67,5°	67,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	100,1	100,1	100,1	100,1
Wheelbase (mm)	1134	1157	1192	1215
Chain Stay Length (mm)	438	438	438	438
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	612	612	635	668
Reach (mm)	406	429	454	471
Stand Over Height (mm)	730	734	763	782
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.