



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Copper Coin, Panther
CUADRO	ALUXX-grade aluminum, 125mm FlexPoint suspension, 12x148mm thru-axle
TIJERA	Crest 34 SL RCL, 140mm, Boost 15x110 QR
AMORTIGUADOR	Suntour Raidon R, 190x45
COMPONENTES	
MANUBRIO	Giant Contact SL TR35, 780x35mm
GRIPS	Giant Sole-O
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
POSTE DE ASIENTO	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
ASIENTO	Giant Romero
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano CUES SL-6000, 1x10
DESVIADOR	N/A
CAMBIO TRASERO	Shimano CUES RD-U6000
FRENOS	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
PALANCAS DE FRENOS	Shimano MT-401
CASSETTE	Shimano CUES, CS-LG300, 11x48
CADENA	KMC X-11
MULTIPLICACIÓN	Shimano CUES FC-U6000, 30t S:170mm, M:170mm, L:170mm, XL:170mm
EJE DE CENTRO	Shimano, threaded

RUEDAS	
RUEDAS	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MAZAS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, HG driver body
RAYOS	Sapim, 28, J-bend
NEUMÁTICOS	[F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Dissector 29x2.4 WT, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.4", max chainring size 32t

Precio: \$50,990.00

GEOMETRÍA

CUADRO	S	M	L	XL
Longitud de la Base del Poste de Asiento (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	217	242	268	293
Ángulo de la Base del Poste de Asiento	76.5°	76.5°	76.5°	76.5°
Longitud del Tubo Superior (mm)	563	595	622	654
Longitud del Telescopio (mm)	100	110	120	125
Ángulo del Telescopio	65.5°	65.5°	65.5°	65.5°
Rake (mm)	44	44	44	44
Trail (mm)	124.4	124.4	124.4	124.4
Distancia entre Ejes (mm)	1164	1198	1227	1260
Longitud de Vaina Inferior (mm)	440	440	440	440
Caída del Eje de Centro (mm)	40	40	40	40
Stack (mm)	614	623	632	636
Reach (mm)	415	445	470	500
Altura del Tubo Superior al Suelo (mm)	735	734	753	758
Ancho del Manubrio (mm)	780	780	780	780
Longitud de la Potencia (mm)	40	40	50	50
Longitud de la Biela (mm)	165	170	170	170
Tamaño de las Ruedas	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Todas las especificaciones están sujetas a cambios sin previo aviso.