

STANCE E+ 0



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
BATTERI	Giant EnergyPak 800Wh
LADER	Giant EnergyPak 4A smart charger
RAMME	
STØRRELSER	S, M, L, XL
FARVER	Deep Lake/Black
RAMME	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (Z562/Z572)
FORGAFFEL	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
BAGDÆMPER	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMPONENTER	
STYR	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GREB / STYRBÅND	Giant Tactal Pro single lock-on
FREMPIND	Giant Contact SL 35
SADELPIND	Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170mm, L/XL: 170~200mm)
SADEL	Giant Contact Ergo Trail
PEDALER	Large platform pedal, 28-pins, PP cage, Steel axle
GEARGRUPPE	
SKIFTEGREB	Shimano Cues LinkGlide
BAGSKIFTER	Shimano Deore XT 11-speed Shadow+
BREMSE	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
BREMSEGREB	Shimano Deore XT BL-M8100
KASSETTE	Shimano Cues LinkGlide, 11-speed, 11-50T
KÆDE	Shimano LinkGlide
KRANKSÆT	Forged aluminum crank arms

HJUL	
FÆLGE	Giant TRA2, Tubeless ready, 30mm inner width
NAV	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
EGER	Sapim Race
DÆK	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
EKSTRA	Tubeless kit (liquid, valves, levers, manual, tool)
TILBEHØR	
LÅS	Torx 25 Battery Lock with built-in Torque limiter
SKÆRM / KÆDESKÆRM	MRP 1x HD guide, CS e-Mount, 32~38T Adjustable
GRÆNSER	
MAX KLINGE STØRRELSE	Direct-mount steel 36T (maximum: 38T)

Pris: 44.599,00 kr.

GEOMETRI

RAMME	S	M	L	XL
Sadelrørlængde (mm)	400	425	450	475
Sadelpindindsætningsdybde (mm)	235	260	285	310
Sadelrørvinkel	76,5°	76,5°	76,5°	76,5°
Overrørs længde (mm)	579	606	635	663
Kronrørs længde (mm)	100	115	130	145
Kronrøsvinkel	64,5°	64,5°	64,5°	64,5°
Forgaffel fremspring (rake) (mm)	44	44	44	44
Sti (mm)	132	132	132	132
Akselafstand (mm)	1229	1259	1291	1322
Kædestagslængde (mm)	468	468	468	468
Krankboks drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Skridthøjde (mm)	746	744	756	762
Styrbredde (mm)	780	780	780	780
Frempindslængde (mm)	40	40	40	40
Pedalarmslængde (mm)	165	165	165	165
Hjulstørrelse	29"	29"	29"	29"

Alle de anførte specifikationer kan ændres uden varsel.