

# STANCE E+ 0

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Pro3X, 36v, 100Nm, 800W peak power, PedalPlus 6-Sensor technology
<b>CONTROLLER</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
<b>DISPLAY</b>	Giant RideControl Dash 2, full colour LCD display
<b>BATTERY</b>	EnergyPak Smart 800Wh, EnergyPak Plus 200/240Wh range extender compatible
<b>CHARGER</b>	Giant EnergyPak 4A smart charger
<b>MAXIMUM ASSISTED SPEED</b>	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Deep Lake/Black
<b>FRAME</b>	ALUXX SL-grade aluminium, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDH, KSA40 compatible
<b>FORK</b>	Fox 36 Rhythm E-Tuned, 150mm travel, 44mm offset, GRIP damper, Boost Kabolt-X 110x15mm
<b>SHOCK</b>	Fox Float X Factory, EVOL Large Volume sleeve, 2 position lever, custom tuned
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 20mm Rise
<b>GRIPS</b>	Giant Tactal Pro single lock-on
<b>STEM</b>	Giant Contact SL 35mm S:40mm, M:40mm, L:50mm, XL:50mm
<b>SEATPOST</b>	GiantContact Switch AT travel-adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
<b>SADDLE</b>	Giant Contact Ergo Trail
<b>PEDALS</b>	Platform
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano CUES, SL-6000, 1x11
<b>REAR DERAILLEUR</b>	Shimano Deore XT 11-speed Shadow+
<b>BRAKES</b>	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
<b>BRAKE LEVERS</b>	Shimano Deore XT BL-M8100
<b>CASSETTE</b>	Shimano Cues LinkGlide, 11-speed, 11-50T
<b>CHAIN</b>	Shimano Cues LinkGlideCN-LG500
<b>CRANKSET</b>	Forged aluminium crank arms Steel direct mount, 36T chain ring S:165mm, M: 165mm, L:165mm, XL:165mm
<b>BOTTOM BRACKET</b>	N/A

WHEELS	
<b>RIMS</b>	Giant TRA2 Hookless Tubeless ready Alloy 29" 30mm inner width
<b>HUBS</b>	Giant E-Drive 260Nm, 72T engagement, boost, 15x110mm [F] 12x148mm [R], e-bike optimised, 28H
<b>SPOKES</b>	Sapim Race
<b>TYRES</b>	[F] Maxxis Minion DHF 29.x2.5 WT, TLR, EXO, 3C Maxx Terra, tubeless, [R] Maxxis Dissector 29x2.4 WT, TLR, EXO+, tubeless
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
<b>LOCK</b>	Torx 25 Battery Lock with built-in Torque limiter
<b>FENDER/CHAINGUARD</b>	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITS	
<b>MAX CHAINRING SIZE</b>	Direct-mount steel 36T (maximum: 38T)

**Price: \$8,999.00**

## GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Seat Tube Angle	76.5°	76.5°	76.5°	76.5°
Top Tube Length (mm)	579	606	635	663
Head Tube Length (mm)	100	115	130	145
Head Tube Angle	64.5°	64.5°	64.5°	64.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Wheelbase (mm)	1229	1259	1291	1322
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stand Over Height (mm)	746	744	756	762
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.