

# STANCE E+ 0

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY (PEDAL ASSIST)	
<b>MOTOR</b>	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
<b>CONTROLLER</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
<b>DISPLAY</b>	Giant RideControl Dash 2, full color LCD display
<b>BATTERY</b>	Giant EnergyPak 800Wh
<b>CHARGER</b>	Giant EnergyPak 4A smart charger
FRAME	
<b>SIZES</b>	S, M, L, XL
<b>FRAME</b>	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (ZS62/ZS72)
<b>FORK</b>	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
<b>SHOCK</b>	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
COMPONENTS	
<b>HANDLEBAR</b>	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
<b>GRIPS</b>	Giant Tactal Pro single lock-on
<b>STEM</b>	Giant Contact SL 35
<b>SEATPOST</b>	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
<b>SADDLE</b>	Giant Contact Ergo Trail
<b>PEDALS</b>	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Cues LinkGlide
<b>REAR DERAILLEUR</b>	Shimano Deore XT 11-speed Shadow+
<b>BRAKES</b>	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
<b>BRAKE LEVERS</b>	Shimano Deore XT BL-M8100
<b>CASSETTE</b>	Shimano Cues LinkGlide, 11-speed, 11-50T
<b>CHAIN</b>	Shimano LinkGlide
<b>CRANKSET</b>	Forged aluminum crank arms

WHEELS	
<b>RIMS</b>	Giant TRA2, Tubeless ready, 30mm inner width
<b>HUBS</b>	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
<b>SPOKES</b>	Sapim Race
<b>TYRES</b>	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
<b>LOCK</b>	Torx 25 Battery Lock with built-in Torque limiter
<b>FENDER/CHAINGUARD</b>	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITS	
<b>MAX CHAINRING SIZE</b>	Direct-mount steel 36T (maximum: 38T)

**Price: £4,999.00**

## GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Seat Tube Angle	76.5°	76.5°	76.5°	76.5°
Top Tube Length (mm)	579	606	635	663
Head Tube Length (mm)	100	115	130	145
Head Tube Angle	64.5°	64.5°	64.5°	64.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Wheelbase (mm)	1229	1259	1291	1322
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stand Over Height (mm)	746	744	756	762
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29"	29"	29"	29"

*Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.*