

STANCE E+ 0

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
BATTERY	Giant EnergyPak 800Wh
CHARGER	Giant EnergyPak 4A smart charger
FRAME	
SIZES	S, M, L, XL
FRAME	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (ZS62/ZS72)
FORK	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
SHOCK	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
COMPONENTS	
HANDLEBAR	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GRIPS	Giant Tactal Pro single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SADDLE	Giant Contact Ergo Trail
PEDALS	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVETRAIN	
SHIFTERS	Shimano Cues LinkGlide
REAR DERAILLEUR	Shimano Deore XT 11-speed Shadow+
BRAKES	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	Shimano Cues LinkGlide, 11-speed, 11-50T
CHAIN	Shimano LinkGlide
CRANKSET	Forged aluminum crank arms

WHEELS	
RIMS	Giant TRA2, Tubeless ready, 30mm inner width
HUBS	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
SPOKES	Sapim Race
TIRES	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter
FENDER/CHAINGUARD	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITS	
MAX CHAINRING SIZE	Direct-mount steel 36T (maximum: 38T)

Recommended Retail Price: \$6,000.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (inch)	15.7	16.7	17.7	18.7
Seat Post Insertion Depth (inch)	9.3	10.2	11.2	12.2
Seat Tube Angle	76.5°	76.5°	76.5°	76.5°
Top Tube Length (inch)	22.8	23.9	25	26.1
Head Tube Length (inch)	3.9	4.5	5.1	5.7
Head Tube Angle	64.5°	64.5°	64.5°	64.5°
Fork Rake (inch)	1.7	1.7	1.7	1.7
Trail (inch)	5.2	5.2	5.2	5.2
Wheelbase (inch)	48.4	49.6	50.8	52
Chain Stay Length (inch)	18.4	18.4	18.4	18.4
Bottom Bracket Drop (inch)	1	1	1	1
Stack (inch)	24.2	24.7	25.2	25.8
Reach (inch)	17	17.9	18.9	19.9
Stand Over Height (inch)	29.4	29.3	29.8	30
Handlebar Width (inch)	30.7	30.7	30.7	30.7
Stem Length (inch)	1.6	1.6	2	2
Crank Length (inch)	6.5	6.5	6.5	6.5
Wheel Size	29"	29"	29"	29"

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*