

STANCE E+ 0



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
OHJAUSYKSIKKÖ	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
NÄYTTÖ	Giant RideControl Dash 2, full color LCD display
AKKU	Giant EnergyPak 800Wh
LATURI	Giant EnergyPak 4A smart charger
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Deep Lake/Black
RUNKO	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (Z562/Z572)
HAARUKKA	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
ISKUNVAIMENNIN	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMONENTIT	
OHJAUSTANKO	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GRIPIT	Giant Tactal Pro single lock-on
OHJAINKANNATIN	Giant Contact SL 35
SATULATOLPPA	Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170mm, L/XL: 170~200mm)
SATULA	Giant Contact Ergo Trail
POLKIMET	Large platform pedal, 28-pins, PP cage, Steel axle
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Cues LinkGlide
TAKAVAIHTAJA	Shimano Deore XT 11-speed Shadow+
JARRUT	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
JARRUKAHVAT	Shimano Deore XT BL-M8100
RATASPAKKA	Shimano Cues LinkGlide, 11-speed, 11-50T
KETJUT	Shimano LinkGlide
KAMPISARJA	Forged aluminum crank arms

RENKAAT	
VANTEET	Giant TRA2, Tubeless ready, 30mm inner width
NAVAT	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
PINNAT	Sapim Race
RENKAAT	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
LISÄTIEDOT	Tubeless kit (liquid, valves, levers, manual, tool)
TARVIKKEET	
LUKKO	Torx 25 Battery Lock with built-in Torque limiter
KETJUNSUOJA	MRP 1x HD guide, CS e-Mount, 32~38T Adjustable
RAJOITTEET	
MAX KETJUN KOKO	Direct-mount steel 36T (maximum: 38T)

Suositus hinta: 5 999,00 €

GEOMETRIA

RUNKO	S	M	L	XL
Satulaputken pituus (mm)	400	425	450	475
Satulatolpan asennussyvyys (mm)	235	260	285	310
Satulaputken kulma	76,5°	76,5°	76,5°	76,5°
Vaakaputken pituus (mm)	579	606	635	663
Emäputken pituus (mm)	100	115	130	145
Emäputken kulma	64,5°	64,5°	64,5°	64,5°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	132	132	132	132
Akseliväli (mm)	1229	1259	1291	1322
Takahaarukan alaputken pituus (mm)	468	468	468	468
Keskiön pudotus (mm)	26	26	26	26
Stack-mitta (mm)	614	628	641	655
Reach-mitta (mm)	431	455	480	505
Standover-mitta (mm)	746	744	756	762
Ohjaustangon leveys (mm)	780	780	780	780
Ohjainkannattimen pituus (mm)	40	40	40	40
Kammen pituus (mm)	165	165	165	165
Rengaskoko	29"	29"	29"	29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.