

STANCE E+ 0

GIANT



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
COMMANDE	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
ECRAN	Giant RideControl Dash 2, full color LCD display
BATTERIE	Giant EnergyPak 800Wh
ENERGYPAK PLUS COMPATIBLES	EnergyPakPlus 200 & 250Wh
CHARGEUR	Giant EnergyPak 4A smart charger
CONNECTIVITÉ	E-Lock, FindMyBike
CADRE	
TAILLES	S, M, L, XL
COLORIS	Deep Lake/ Black
CADRE	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derrailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (Z562/Z572)
FOURCHE	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
AMORTISSEUR	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
COMPOSANTS	
CINTRE	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
POIGNÉES	Giant Tactal Pro single lock-on
POTENCE	Giant Contact SL, 35
TIGE DE SELLE	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SELLE	Giant Contact Ergo Trail
PÉDALES	Large platform pedal, 28-pins, PP cage, Steel axle
DÉRAILLEUR	
MANETTES	Shimano Cues LinkGlide
DÉRAILLEUR ARRIÈRE	Shimano Deore XT 11-speed Shadow+
FREINS	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
LEVIERS DE FREIN	Shimano Deore XT BL-M8100
CASSETTE	Shimano LinkGlide, 11speed, 11-50T
CHAÎNE	Shimano LinkGlide
PÉDALIER	Direct-mount steel FSA 36T (maximum: 38T), Forged Aluminium crank arm set 165mm, Q-Factor:168mm

ROUES	
JANTES	Giant TRA2, Tubeless ready, 30mm inner width
MOYEUX	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
RAYONS	Sapim Race
PNEUS	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
EXTRAS	Tubeless kit (liquide, valves, leviers, manual, tool)
LIMITES	
COMPATIBILITY	Tire Checker Aegis
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
GARDE-BOUE / CHAÎNE	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITES	
POIDS TOTAL MAX AUTORISÉ	140kg
TAILLE MAXIMALE DU PLATEAU	Direct-mount steel 36T (maximum: 38T)

Prix Public Conseillé: 5 500,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Angle de tube de selle	76,5°	76,5°	76,5°	76,5°
Longueur du tube supérieur (mm)	579	606	635	663
Longueur du tube de direction (mm)	100	115	130	145
Angle du tube de direction	64,5°	64,5°	64,5°	64,5°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Empattement (mm)	1229	1259	1291	1322
Longueur des bases (mm)	468	468	468	468
Drop du boîtier de pédalier (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Hauteur en statique (mm)	746	744	756	762
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	40	40	50	50
Longueur des manivelles (mm)	165	165	165	165
Diamètre des roues	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.