

STANCE E+ 0

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
COMANDO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
BATTERIA	Giant EnergyPak 800Wh
CARICATORE	Giant EnergyPak 4A smart charger
TELAIO	
TAGLIE	S, M, L, XL
TELAIO	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (ZS62/ZS72)
FORCELLA	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
AMMORTIZZATORE	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
COMPONENTISTICA	
MANUBRIO	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
MANOPOLE	Giant Tactal Pro single lock-on
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISSELLA	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SELLA	Giant Contact Ergo Trail
PEDALI	Large platform pedal, 28-pins, PP cage, Steel axle
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Cues LinkGlide
DERAGLIATORE POSTERIORE	Shimano Deore XT 11-speed Shadow+
FRENI	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
COMANDI FRENO	Shimano Deore XT BL-M8100
PACCO PIGNONI	Shimano Cues LinkGlide, 11-speed, 11-50T
CATENA	Shimano LinkGlide
GUARNITURA	Forged aluminum crank arms

RUOTE	
CERCHI	Giant TRA2, Tubeless ready, 30mm inner width
MOZZI	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
RAGGI	Sapim Race
COPERTONI	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
LUCCHETTO	Torx 25 Battery Lock with built-in Torque limiter
PARAFANGO / PARACATENA	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITI	
DIMENSIONE MASSIMA DELLA CORONA	Direct-mount steel 36T (maximum: 38T)

Prezzo: 5.299,00 €

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza Tubo Sella (mm)	400	425	450	475
Profondità inserimento reggisella (mm)	235	260	285	310
Angolo Tubo Sella	76,5°	76,5°	76,5°	76,5°
Lunghezza Tubo Orizzontale (mm)	579	606	635	663
Lunghezza Tubo Sterzo (mm)	100	115	130	145
Angolo Sterzo	64,5°	64,5°	64,5°	64,5°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	132	132	132	132
Interasse (mm)	1229	1259	1291	1322
Lunghezza Carro Posteriore (mm)	468	468	468	468
Drop Movimento Centrale (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Altezza stand over (mm)	746	744	756	762
Larghezza Manubrio c/c (mm)	780	780	780	780
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	165	165	165	165
Dimensione Ruote	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.