



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
OVLÁDAČ	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
OVLÁDACIA JEDNOTKA	Giant RideControl Dash 2, full color LCD display
BATÉRIA	Giant EnergyPak 800Wh
NABÍJAČKA	Giant EnergyPak 4A smart charger
RÁM	
VELKOSTI	S, M, L, XL
RÁM	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (ZS62/ZS72)
VIDLICA	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
TLMIČ	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMPONENTY	
RIADIDLÁ	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GRIPY	Giant Tactal Pro single lock-on
PREDSTAVEC	Giant Contact SL 35
SEDLOVKA	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SEDADLO	Giant Contact Ergo Trail
PEDÁLE	Large platform pedal, 28-pins, PP cage, Steel axle
POHON	
RADENIE	Shimano Cues LinkGlide
PREHADZOVAČKA	Shimano Deore XT 11-speed Shadow+
BRZDY	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
BRZDOVÉ PÁKY	Shimano Deore XT BL-M8100
KAZETA	Shimano Cues LinkGlide, 11-speed, 11-50T
REŤAZ	Shimano LinkGlide
KLUKY	Forged aluminum crank arms

KOLESÁ	
RÁFIKY	Giant TRA2, Tubeless ready, 30mm inner width
NÁBOJE	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
ŠPICE	Sapim Race
PNEUMATIKY	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
DOPLNKY	Tubeless kit (liquid, valves, levers, manual, tool)
PRÍSLUŠENSTVO	
ZAMKNÚŤ	Torx 25 Battery Lock with built-in Torque limiter
BLATNÍK / CHRÁNIČ REŤAZE	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITY	
MAXIMÁLNA VEĽKOSŤ REŤAZE	Direct-mount steel 36T (maximum: 38T)

Cena: 5 599 €

GEOMETRIA

RÁM	S	M	L	XL
Dĺžka sedlovej trubky (mm)	400	425	450	475
Hĺbka vloženia sedlovky (mm)	235	260	285	310
Uhol sedlovej trubky	76,5°	76,5°	76,5°	76,5°
Dĺžka hornej rámovej trubky (mm)	579	606	635	663
Dĺžka hlavovej trubky (mm)	100	115	130	145
Uhol hlavovej trubky	64,5°	64,5°	64,5°	64,5°
Offset vidlice (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Rázvor (mm)	1229	1259	1291	1322
Dĺžka zadnej stavby (mm)	468	468	468	468
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	26	26	26	26
Stack - výška riadenia (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Výška rámu od zeme (mm)	746	744	756	762
Šírka riaditok (mm)	780	780	780	780
Dĺžka predstavca (mm)	40	40	50	50
Dĺžka klúku (mm)	165	165	165	165
Rozmer kolies	29"	29"	29"	29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.