

STANCE E+ 0

GIANT



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
VISA	Giant RideControl Dash 2, full color LCD display
BATTERI	Giant EnergyPak 800Wh
LADDARE	Giant EnergyPak 4A smart charger
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Deep Lake/Black
RAM	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (Z562/Z572)
GAFFEL	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
BAKDÄMPARE	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMPONENTER	
STYRE	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GREPPAR	Giant Tactal Pro single lock-on
STAM	Giant Contact SL 35
SADELSTOLPE	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SADEL	Giant Contact Ergo Trail
PEDALER	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVLINJA	
VÄXLAR	Shimano Cues LinkGlide
BAKVÄXEL	Shimano Deore XT 11-speed Shadow+
BROMSAR	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
BROMSSPAKAR	Shimano Deore XT BL-M8100
KASSETT	Shimano Cues LinkGlide, 11-speed, 11-50T
KEDJA	Shimano LinkGlide
VEVPARTI	Forged aluminum crank arms

HJUL	
FÄLGAR	Giant TRA2, Tubeless ready, 30mm inner width
NAV	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
EKRAR	Sapim Race
DÄCK	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO+ [R]
EXTRAFUNKTIONER	Tubeless kit (liquid, valves, levers, manual, tool)
TILLBEHÖR	
LÅSA	Torx 25 Battery Lock with built-in Torque limiter
STÄNKSKÄRM/KEDJESKYDD	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
GRÄNSER	
MAX KEDJERINGSTORLEK	Direct-mount steel 36T (maximum: 38T)

Price: 67 990,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Vinkel sadelrör	76,5°	76,5°	76,5°	76,5°
Topprörets längd (mm)	579	606	635	663
Styrhuvud Längd (mm)	100	115	130	145
Vinkel styrhuvud	64,5°	64,5°	64,5°	64,5°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	132	132	132	132
Hjulbas (mm)	1229	1259	1291	1322
Kedjestagslängd (mm)	468	468	468	468
Nedre fäste Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stå över höjden (mm)	746	744	756	762
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	40	40	50	50
Vevlängd (mm)	165	165	165	165
Hjulstorlek	29"	29"	29"	29"

All specifications listed are subject to change without notice.