

STANCE E+ 1

GIANT



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
STEUEREINHEIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
AKKU	Giant EnergyPak 800Wh
CHARGER	Giant EnergyPak 4A smart charger
RAHMEN	
GRÖSSEN	S, M, L, XL
RAHMEN	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Deraillieur hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (ZS62/ZS72)
GABEL	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
DÄMPFER	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMPONENTEN	
LENKER	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GRIFFE	Giant Tactal Pro single lock-on
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170m, L/XL: 170~200mm)
SATTEL	Giant Contact Ergo Trail
PEDALE	Large platform pedal, 28-pins, PP cage, Steel axle
ANTRIEB	
SCHALTHEBEL	Shimano Cues LinkGlide
SCHALTWERK	Shimano Cues LinkGlide, 10-speed, Shadow+
BREMSEN	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BREMSHEBEL	Shimano Deore, BL-M401
KASSETTE	Shimano Cues LinkGlide, 10-speed, 11-48T
KETTE	Shimano LinkGlide
KURBEL	Forged aluminum crank arms

LAUFRÄDER	
FELGEN	Giant AM30, Tubeless ready, 30mm inner width
NABE	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
SPEICHEN	Stainless Steel
REIFEN	Maxxis Minion DHF 29X2.50''' WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40''' WT Foldable TLR EXO [R]
ACCESSORIES	
SCHLOSS	Torx 25 Battery Lock with built-in Torque limiter
SCHUTZBLECHE/KETTENSCHUTZ	MRP 1x HD guide, CS e-Mount, 32~38T Adjustable
LIMITS	
MAX CHAINRING SIZE	Direct-mount steel 36T (maximum: 38T)

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Sitzrohrwinkel	76.5°	76.5°	76.5°	76.5°
Oberrohrlänge (mm)	579	606	635	663
Steuerrohr-Länge (mm)	100	115	130	145
Steuerrohr-Winkel	64.5°	64.5°	64.5°	64.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Radstand (mm)	1229	1259	1291	1322
Kettenstreben-Länge (mm)	468	468	468	468
Tretlager-Höhe (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Überstandshöhe (mm)	746	744	756	762
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	40	40
Kurbellänge (mm)	165	165	165	165
Radgröße	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.