

STANCE E+ 1

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X, 36v, 100Nm, 800W peak power, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full colour LCD display
BATTERY	EnergyPak Smart 800Wh, EnergyPak Plus 200/240Wh range extender compatible
CHARGER	Giant EnergyPak 4A smart charger
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
FRAME	
SIZES	S, M, L, XL
COLOURS	Almond/Black
FRAME	ALUXX SL-grade aluminium, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDH, KSA40 compatible
FORK	Giant STL 36 Air, 150mm travel, 5-position compression adjust, e-bike optimised, 110x15mm Boost axle, full fender compatible
SHOCK	Giant Crest FloTrac, 3-position lever, e-bike optimised
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm Rise
GRIPS	Giant Tactal Pro single lock-on
STEM	Giant Contact SL 35mm S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch AT travel-adjustable dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Contact Ergo Trail
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano CUES, SL-6000, 1x10
REAR DERAILLEUR	Shimano Cues U6000, 10-speed, Shadow+
BRAKES	Shimano BR-M420, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BRAKE LEVERS	Shimano Deore, BL-M401
CASSETTE	Shimano Cues LinkGlide LG-30010, 10-speed, 11-48T
CHAIN	Shimano Cues LinkGlideCN-LG500
CRANKSET	Forged aluminium crank arms Steel direct mount, 36T chain ring S:165mm, M: 165mm, L:165mm, XL:165mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM Tubeless ready Alloy 29" Tubeless ready
HUBS	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R], 32H
SPOKES	Stainless
TYRES	[F] Maxxis Minion DHF 29.x2.5 WT, TLR, EXO, tubeless, [R] Maxxis Dissector 29x2.4 WT, TLR, EXO, tubeless
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter
FENDER/CHAINGUARD	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITS	
MAX CHAINRING SIZE	Direct-mount steel 36T (maximum: 38T)

Price: \$7,499.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Seat Tube Angle	76.5°	76.5°	76.5°	76.5°
Top Tube Length (mm)	579	606	635	663
Head Tube Length (mm)	100	115	130	145
Head Tube Angle	64.5°	64.5°	64.5°	64.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Wheelbase (mm)	1229	1259	1291	1322
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stand Over Height (mm)	746	744	756	762
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.