

STANCE E+ 1



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
OHJAUSYKSIKKÖ	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
NÄYTTÖ	Giant RideControl Dash 2, full color LCD display
AKKU	Giant EnergyPak 800Wh
LATURI	Giant EnergyPak 4A smart charger
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Almond (matte)
RUNKO	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (Z562/Z572)
HAARUKKA	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
ISKUNVAIMENNIN	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMONENTIT	
OHJAUSTANKO	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GRIPIT	Giant Tactal Pro single lock-on
OHJAINKANNATIN	Giant Contact SL 35
SATULATOLPPA	Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170m, L/XL: 170~200mm)
SATULA	Giant Contact Ergo Trail
POLKIMET	Large platform pedal, 28-pins, PP cage, Steel axle
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Cues LinkGlide
TAKAVAIHTAJA	Shimano Cues LinkGlide, 10-speed, Shadow+
JARRUT	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
JARRUKAHVAT	Shimano Deore, BL-M401
RATASPAKKA	Shimano Cues LinkGlide, 10-speed, 11-48T
KETJUT	Shimano LinkGlide
KAMPISARJA	Forged aluminum crank arms

RENKAAT	
VANTEET	Giant AM30, Tubeless ready, 30mm inner width
NAVAT	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
PINNAT	Stainless Steel
RENKAAT	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO [R]
TARVIKKEET	
LUKKO	Torx 25 Battery Lock with built-in Torque limiter
KETJUNSUOJA	MRP 1x HD guide, CS e-Mount, 32~38T Adjustable
RAJOITTEET	
MAX KETJUN KOKO	Direct-mount steel 36T (maximum: 38T)

Suositusinta: 4 899,00 €

GEOMETRIA

RUNKO	S	M	L	XL
Satulaputken pituus (mm)	400	425	450	475
Satulatolpan asennussyvyys (mm)	235	260	285	310
Satulaputken kulma	76,5°	76,5°	76,5°	76,5°
Vaakaputken pituus (mm)	579	606	635	663
Emäputken pituus (mm)	100	115	130	145
Emäputken kulma	64,5°	64,5°	64,5°	64,5°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	132	132	132	132
Akseliväli (mm)	1229	1259	1291	1322
Takahaarukan alaputken pituus (mm)	468	468	468	468
Keskiön pudotus (mm)	26	26	26	26
Stack-mitta (mm)	614	628	641	655
Reach-mitta (mm)	431	455	480	505
Standover-mitta (mm)	746	744	756	762
Ohjaustangon leveys (mm)	780	780	780	780
Ohjainkannattimen pituus (mm)	40	40	40	40
Kammen pituus (mm)	165	165	165	165
Rengaskoko	29"	29"	29"	29"

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.