

STANCE E+ 1

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
ACCU	Giant EnergyPak 800Wh
LADER	Giant EnergyPak 4A smart charger
FRAME	
MATEN	S, M, L, XL
KLEUREN	Almond (matte)
FRAME	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (Z562/Z572)
VOORVORK	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
DEMPER	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)
ONDERDELEN	
STUUR	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
HANDVATTEN	Giant Tactal Pro single lock-on
STUURPEN	Giant Contact SL 35
ZADELLEN	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
ZADEL	Giant Contact Ergo Trail
PEDALEN	Large platform pedal, 28-pins, PP cage, Steel axle
AFMONTAGE	
SHIFTERS	Shimano Cues LinkGlide
ACHTERDERAILLEUR	Shimano Cues LinkGlide, 10-speed, Shadow+
REMMEN	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
REMHENDELS	Shimano Deore, BL-M401
CASSETTE	Shimano Cues LinkGlide, 10-speed, 11-48T
AANDRIJVING	Shimano LinkGlide
CRANKSET	Forged aluminum crank arms

WIELSET	
VELGEN	Giant AM30, Tubeless ready, 30mm inner width
NAVEN	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
SPAKEN	Stainless Steel
BANDEN	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO [R]
ACCESSOIRES	
SLOT	Torx 25 Battery Lock with built-in Torque limiter
SPATBORD/ KETTINGKAST	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITS	
MAXIMALE KETTINGBLADMAAT	Direct-mount steel 36T (maximum: 38T)

Adviesprijs: € 4.599,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Zitbuis Hoek	76,5°	76,5°	76,5°	76,5°
Frame Lengte (horizontaal) (mm)	579	606	635	663
Balhoofdbuis Lengte (mm)	100	115	130	145
Balhoofdbuis Hoek	64,5°	64,5°	64,5°	64,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	132	132	132	132
Wielbasis (mm)	1229	1259	1291	1322
Liggende achtervork lengte (mm)	468	468	468	468
Bottom Bracket Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stand Over Height (mm)	746	744	756	762
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	40	40	50	50
Cranklengte (mm)	165	165	165	165
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.