



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
COMANDO	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARICATORE	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Cordovan
TELAIO	ALUXX SL-grade aluminum, 1.5"-1.8" head tube,125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
FORCELLA	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
AMMORTIZZATORE	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser 31.8x780mm
MANOPOLE	Giant Tactal single lock-on
ATTACCO MANUBRIO	Giant Contact
REGGISSELLA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SELLA	Giant Sport
PEDALI	Flat pedal
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore
DERAGLIATORE ANTERIORE	MRP HD2 co-moulded chain guide
DERAGLIATORE POSTERIORE	Shimano Deore 12-speed
FRENI	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Tektro HD-M745 Orion
PACCO PIGNONI	Shimano CS-M6100-12, 10-51T, 12-speed
CATENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GUARNITURA	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
MOVIMENTO CENTRALE	n/a

RUOTE	
CERCHI	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOZZI	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAGGI	Sapim E-Lite [R] Race [F], e-bike optimized
COPERTONI	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
ILLUMINAZIONE	-
LUCCHETTO	Torx 25 Battery Lock with built-in Torque limiter
PORTAPACCHI	-

Prezzo: € 4.699

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza Tubo Sella (mm)	400	425	450	475
Angolo Tubo Sella	76,0°	76,0°	76,0°	76,0°
Lunghezza Tubo Orizzontale (mm)	580	607	639	671
Lunghezza Tubo Sterzo (mm)	105	115	125	135
Angolo Sterzo	65,5°	65,5°	65,5°	65,5°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	124	124	124	124
Interasse (mm)	1204	1233	1267	1301
Lunghezza Carro Posteriore (mm)	468	468	468	468
Drop Movimento Centrale (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Altezza stand over (mm)	760	760	780	796
Larghezza Manubrio c/c (mm)	780	780	780	780
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	165	165	165	165
Dimensione Ruote	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.