

STANCE E+ 1 PRO

GIANT



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
COMMANDE	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
ECRAN	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGEUR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITÉ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Cordovan
CADRE	ALUXX SL-grade aluminum, 1.5"-1.8" head tube, 125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
FOURCHE	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
AMORTISSEUR	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Connect TR Riser 31.8x780mm
POIGNÉES	Giant Tactal single lock-on
POTENCE	Giant Contact
TIGE DE SELLE	OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170-140MM / 172D-CONTAC-0050 total length 530 T200-170MM
SELLE	Giant Sport
PÉDALES	Flat pedal
DÉRAILLEUR	
MANETTES	Shimano Deore
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore 12-speed
FREINS	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
LEVIER DE FREIN	Tektro HD-M745 Orion
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOYEURS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
PORTE-BAGAGES	-
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 5 000,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	400	425	450	475
Angle de tube de selle	76,0°	76,0°	76,0°	76,0°
Longueur du tube supérieur (mm)	580	607	639	671
Longueur du tube de direction (mm)	105	115	125	135
Angle du tube de direction	65,5°	65,5°	65,5°	65,5°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Empattement (mm)	1204	1233	1267	1301
Longueur des bases (mm)	468	468	468	468
Drop du boîtier de pédalier (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Hauteur en statique (mm)	760	760	780	796
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	40	40	50	50
Longueur des manivelles (mm)	165	165	165	165
Diamètre des roues	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.