



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
PRIKAZ	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Cordovan
OKVIR	ALUXX SL-grade aluminum, 1.5"-1.8" head tube,125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
VILICA	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
AMORTIZER	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
KOMPONENTE	
VOLAN	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal single lock-on
LULA VOLANA	Giant Contact
CIJEV SJEDALA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SJEDALO	Giant Sport
PEDALE	Flat pedal
POGON	
RUČICE MJENJAČA	Shimano Deore
PREDNJI MJENJAČ	MRP HD2 co-moulded chain guide
STRAŽNJI MJENJAČ	Shimano Deore 12-speed
KOČNICE	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
RUČICE KOČNICA	Tektro HD-M745 Orion
KAZETA	Shimano CS-M6100-12, 10-51T, 12-speed
LANAC	KMC e.12 Turbo, EcoProteq, e-bike optimized
POGON	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	Giant AM30, Tubeless ready, 30mm inner width, 29"
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
ŽBICE	Sapim E-Lite [R] Race [F], e-bike optimized
GUME	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
DODACI	
DODACI	
SVJETLA	-
LOKOTI	Torx 25 Battery Lock with built-in Torque limiter
NOSAČ	-

GEOMETRIJA

OKVIR	S	M	L	XL
Dužina cijevi sjedala (mm)	400	425	450	475
Kut cijevi sjedala	76,0°	76,0°	76,0°	76,0°
Dužina gornje cijevi (mm)	580	607	639	671
Dužina prednje cijevi (mm)	105	115	125	135
Kut vilice	65,5°	65,5°	65,5°	65,5°
Zakrivljenost vilice (offset) (mm)	44	44	44	44
Staza (mm)	124	124	124	124
Međuosovinski razmak kotača (mm)	1204	1233	1267	1301
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	468	468	468	468
Položaj osovine pogona (mm)	40	40	40	40
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	618	627	636	646
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	425	450	480	510
Prekoračna visina (mm)	760	760	780	796
Širina volana (mm)	780	780	780	780
Dužina lule volana (mm)	40	40	50	50
Dužina poluge pedale (mm)	165	165	165	165
Veličina kotača	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.