



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLORS	Cordovan
FRAME	ALUXX SL-grade aluminum, 1.5"-1.8" head tube,125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
FORK	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
SHOCK	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal single lock-on
STEM	Giant Contact
SEATPOST	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SADDLE	Giant Sport
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore 12-speed
BRAKES	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Tektro HD-M745 Orion
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

WHEELS	
RIMS	Giant AM30, Tubeless ready, 30mm inner width, 29"
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
CARRIER	-

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	76,0°	76,0°	76,0°	76,0°
Top Tube Length (mm)	580	607	639	671
Head Tube Length (mm)	105	115	125	135
Head Tube Angle	65,5°	65,5°	65,5°	65,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Wheelbase (mm)	1204	1233	1267	1301
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Stand Over Height (mm)	760	760	780	796
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.