

STANCE E+ 1 PRO

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 80Nm, powered by Yamaha
BEDIENINGSUNIT	RideControl Dash, full color LCD screen
DISPLAY	RideControl Dash, full color LCD screen
ACCU	EnergyPak Smart 625Wh
FRAME	
MATEN	S, M, L, XL
KLEUREN	Phantom Green
FRAME	ALUXX Aaluminum, 120mm FlexPoint suspension system
VOORVORK	RockShox Recon Silver RL, 130mm travel, Lock-out, Tapered Steerer, 15x110mm Boost, MaxleLite, e-MTB optimized
DEMPER	RockShox Monarch RT DebonAir, High Volume, 184x44mm, custom tuned
ONDERDELEN	
STUUR	Giant Connect TR Riser 31.8x780mm
HANDVATTEN	Giant Tactal single lock-on
STUURPEN	Giant Contact
ZADEL	Giant Contact Switch, dropper, 30,9mm (S:100/M:125/L:150/XL:170)
ZADEL	Giant Romero Trail
PEDALEN	Flatpedal
AFMONTAGE	
SHIFTERS	Shimano Deore
VOORDERAILLEUR	MRP 1X custom "V3" co-molded TR chain guide
ACHTERDERAILLEUR	Shimano Deore 12-speed
REMMEN	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
REMHENDELS	Shimano Deore BL-M4100, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
AANDRIJVING	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

WIELSET	
VELGEN	Giant AM 29", Tubeless ready, 30mm inner width
NAVEN	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPAKEN	Sapim E-Lite [R] Race [F], e-bike optimized
BANDEN	Maxxis Minion DHF 29X2.5" WT 60TPI Foldable, TLR EXO [F]Maxxis Dissector 29X2.40 60TPI Foldable TLR EXO [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
VERLICHTING	-
DRAGER	-

Adviesprijs: € 4.899,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis lengte (mm)	406	432	482	507
Zitbuis hoek	73,5°	73,5°	73,5°	73,5°
Frame Lengte (horizontaal) (mm)	580	600	625	650
Balhoofdbuis Lengte (mm)	100	110	120	135
Balhoofdbuis Hoek	67,0°	67,0°	67,0°	67,0°
Vork Sprong (mm)	40	40	40	40
Naloop (mm)	113,6	113,6	113,6	113,6
Wielbasis (mm)	1166	1187	1213	1240
Liggende achtervork lengte (mm)	475	475	475	475
Bottom Bracket Drop (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Stand Over Height (mm)	741	756	788	792
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	50	50	50	60
Cranklengte (mm)	160	165	165	170
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.