

# STANCE E+ 1 PRO

GIANT



## SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
<b>BEDIENINGSUNIT</b>	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
<b>DISPLAY</b>	Giant RideControl Dash, high-angle visibility, full color LCD display
<b>ACCU</b>	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
<b>LADER</b>	Giant EnergyPak 6A smart charger, 60% in 2:15h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
<b>MATEN</b>	S, M, L, XL
<b>KLEUREN</b>	Cordovan
<b>FRAME</b>	ALUXX SL-grade aluminum, 1.5"-1.8" head tube, 125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
<b>VOORVORK</b>	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
<b>DEMPER</b>	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
ONDERDELEN	
<b>STUUR</b>	Giant Connect TR Riser 31.8x780mm
<b>HANDVATTEN</b>	Giant Tactal single lock-on
<b>STUURPEN</b>	Giant Contact
<b>ZADELLEN</b>	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
<b>ZADEL</b>	Giant Sport
<b>PEDALEN</b>	Flat pedal
AFMONTAGE	
<b>SHIFTERS</b>	Shimano Deore
<b>VOORDERAILLEUR</b>	MRP HD2 co-moulded chain guide
<b>ACHTERDERAILLEUR</b>	Shimano Deore 12-speed
<b>REMMEN</b>	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
<b>REMHENDELS</b>	Tektro HD-M745 Orion
<b>CASSETTE</b>	Shimano CS-M6100-12, 10-51T, 12-speed
<b>AANDRIJVING</b>	KMC e.12 Turbo, EcoProteq, e-bike optimized
<b>CRANKSET</b>	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
<b>BOTTOM BRACKET</b>	n/a

WIELSET	
<b>VELGEN</b>	Giant AM30, Tubeless ready, 30mm inner width, 29"
<b>NAVEN</b>	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
<b>SPAKEN</b>	Sapim E-Lite [R] Race [F], e-bike optimized
<b>BANDEN</b>	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
<b>EXTRA'S</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
<b>VERLICHTING</b>	-
<b>SLOT</b>	Torx 25 Battery Lock with built-in Torque limiter
<b>DRAGER</b>	-

Adviesprijs: € 5.199,00

## GEOMETRIE

FRAME	S	M	L	XL
Zitbuis lengte (mm)	400	425	450	475
Zitbuis hoek	76,0°	76,0°	76,0°	76,0°
Frame Lengte (horizontaal) (mm)	580	607	639	671
Balhoofdbuis Lengte (mm)	105	115	125	135
Balhoofdbuis Hoek	65,5°	65,5°	65,5°	65,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	124	124	124	124
Wielbasis (mm)	1204	1233	1267	1301
Liggende achtervork lengte (mm)	468	468	468	468
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Stand Over Height (mm)	760	760	780	796
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	40	40	50	50
Cranklengte (mm)	165	165	165	165
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.