

STANCE E+ 1 PRO

GIANT



SPECS

Tecnologia Híbrida de Ciclismo	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
ECRÃ	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARREGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
Quadro	
TAMANHOS	S, M, L, XL
CORES	Cordovan
QUADRO	ALUXX SL-grade aluminum, 1.5"-1.8" head tube, 125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
FORQUILHA	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
AMORTECEDORES	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
Componentes	
GUIADOR	Giant Connect TR Riser 31.8x780mm
PUNHOS	Giant Tactal single lock-on
AVANÇO	Giant Contact
ESPIGÃO DE SELIM	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SELIM	Giant Sport
PEDAIS	Flat pedal
Transmissão	
MANETES	Shimano Deore
DESVIADOR DIANTEIRO	MRP HD2 co-moulded chain guide
DESVIADOR TRASEIRO	Shimano Deore 12-speed
TRAVÕES	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
MANÍPULOS DOS TRAVÕES	Tektro HD-M745 Orion
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CORRENTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
CONJUNTO PEDALEIRO	FSA Comet E-Bike crank arm set/FSA MegaTooth Direct-mount 1X steel 36T
MOVIMENTO CENTRAL	n/a

Rodas	
AROS	Giant AM30, Tubeless ready, 30mm inner width, 29"
CUBOS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAIOS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
Acessórios	
LUZES	-
CADEADO	Torx 25 Battery Lock with built-in Torque limiter
PORTA-BICICLETAS	-

Preço: 4 299,00 €

GEOMETRIA

Quadro	S	M	L	XL
Comprimento do tubo do assento (mm)	400	425	450	475
Ângulo do tubo do assento	76,0°	76,0°	76,0°	76,0°
Comprimento do tubo superior (mm)	580	607	639	671
Comprimento do tubo principal (mm)	105	115	125	135
Ângulo do tubo principal	65,5°	65,5°	65,5°	65,5°
Garfo ancinho (mm)	44	44	44	44
Trilha (mm)	124	124	124	124
distância entre eixos (mm)	1204	1233	1267	1301
Comprimento Chain Stay (mm)	468	468	468	468
Suporte inferior (mm)	40	40	40	40
Pilha (mm)	618	627	636	646
Alcançar (mm)	425	450	480	510
Altura do standover (mm)	760	760	780	796
Largura do guidão (mm)	780	780	780	780
Comprimento da haste (mm)	40	40	50	50
Comprimento da Manivela (mm)	165	165	165	165
Tamanho da roda	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.