



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Dash, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
PRIKAZOVALNIK	Giant RideControl Dash, high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Cordovan
OKVIR	ALUXX SL-grade aluminum, 1.5"-1.8" head tube,125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
VILICE	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
AMORTIZER	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
KOMPONENTE	
KRMILO	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal single lock-on
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SEDEŽ	Giant Sport
PEDALA	Flat pedal
POGON	
PRESTAVNE ROČICE	Shimano Deore
PREDNJI MENJALNIK	MRP HD2 co-moulded chain guide
ZADNJI MENJALNIK	Shimano Deore 12-speed
ZAVORE	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
ZAVORNE ROČICE	Tektro HD-M745 Orion
VERIŽNIK	Shimano CS-M6100-12, 10-51T, 12-speed
VERIGA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GONILKE Z VERIŽNIKI	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	Giant AM30, Tubeless ready, 30mm inner width, 29"
PESTA	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
NAPERE	Sapim E-Lite [R] Race [F], e-bike optimized
PLAŠČI	Maxxis Minion DHF 29X2.50"" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40"" Foldable, WT, TLR, EXO, 60TPI [R]
DODATKI	Tubeless kit (liquid, valves, levers, manual, tool)
DODATNA OPREMA	
SVETILA	-
KLJUČAVNICA	Torx 25 Battery Lock with built-in Torque limiter
PRTLJAŽNIK	-

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	400	425	450	475
Kot sedežne cevi	76,0°	76,0°	76,0°	76,0°
Top Tube Length (mm)	580	607	639	671
Višina glave okvirja (mm)	105	115	125	135
Krmilni kot	65,5°	65,5°	65,5°	65,5°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Medosna razdalja (mm)	1204	1233	1267	1301
Dolžina cevi ob verigi (mm)	468	468	468	468
Bottom Bracket Drop (mm)	40	40	40	40
Oddaljenost zgornje cevi od gonilne osi (mm)	618	627	636	646
Doseg (mm)	425	450	480	510
Višina zgornje cevi (mm)	760	760	780	796
Širina krmila (mm)	780	780	780	780
Dolžina opore krmila (mm)	40	40	50	50
Dolžina gonilke (mm)	165	165	165	165
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.