

STANCE E+ 1

GIANT



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
VISA	Giant RideControl Dash 2, full color LCD display
BATTERI	Giant EnergyPak 800Wh
LADDARE	Giant EnergyPak 4A smart charger
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Almond (matte)
RAM	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (Z562/Z572)
GAFFEL	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
BAKDÄMPARE	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMPONENTER	
STYRE	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GREPPAR	Giant Tactal Pro single lock-on
STAM	Giant Contact SL 35
SADELSTOLPE	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SADEL	Giant Contact Ergo Trail
PEDALER	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVLINA	
VÄXLAR	Shimano Cues LinkGlide
BAKVÄXEL	Shimano Cues LinkGlide, 10-speed, Shadow+
BROMSAR	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BROMSSPAKAR	Shimano Deore, BL-M401
KASSETT	Shimano Cues LinkGlide, 10-speed, 11-48T
KEDJA	Shimano LinkGlide
VEVPARTI	Forged aluminum crank arms

HJUL	
FÄLGAR	Giant AM30, Tubeless ready, 30mm inner width
NAV	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
EKRAR	Stainless Steel
DÄCK	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO [R]
TILLBEHÖR	
LÅSA	Torx 25 Battery Lock with built-in Torque limiter
STÄNKSKÄRM/KEDJESKYDD	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
GRÄNSER	
MAX KEDJERINGSTORLEK	Direct-mount steel 36T (maximum: 38T)

Price: 55 990,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Vinkel sadelrör	76,5°	76,5°	76,5°	76,5°
Topprörets längd (mm)	579	606	635	663
Styrhuvud Längd (mm)	100	115	130	145
Vinkel styrhuvud	64,5°	64,5°	64,5°	64,5°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	132	132	132	132
Hjulbas (mm)	1229	1259	1291	1322
Kedjestagslängd (mm)	468	468	468	468
Nedre fäste Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stå över höjden (mm)	746	744	756	762
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	40	40	50	50
Vevlängd (mm)	165	165	165	165
Hjulstorlek	29"	29"	29"	29"

All specifications listed are subject to change without notice.