

STANCE E+ 1



產品規格

HYBRID CYCLING TECHNOLOGY	
電機系統	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
控制系統	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
顯示系統	Giant RideControl Dash 2, full color LCD display
電池系統	Giant EnergyPak 800Wh
CHARGER	Giant EnergyPak 4A smart charger
車架	
尺寸	S, M, L
顏色	杏仁黃
車架	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailler hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (Z562/Z572)
前叉	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
避震器	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)
COMPONENTS	
車把手	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
把手帶/套	Giant Tactal Pro single lock-on
豎桿	Giant Contact SL 35
座桿	Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170m, L/XL: 170~200mm)
坐墊	Giant Contact Ergo Trail
踏板	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVETRAIN	
變速把手	Shimano Cues LinkGlide
後變速器	Shimano Cues LinkGlide, 10-speed, Shadow+
煞車系統	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
煞車把手	Shimano Deore, BL-M401
飛輪	Shimano Cues LinkGlide, 10-speed, 11-48T
鍊條	Shimano LinkGlide
大齒盤	Forged aluminum crank arms

輪組	
輪圈	Giant AM30, Tubeless ready, 30mm inner width
花鼓	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
輻條	Stainless Steel
外胎	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO [R]
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter
FENDER/CHAINGUARD	MRP 1x HD guide, CS e-Mount, 32~38T Adjustable
LIMITS	
MAX CHAINRING SIZE	Direct-mount steel 36T (maximum: 38T)

Price: NT\$148,000

車架幾何

車架	S	M	L
座(立)管長 (mm)	400	425	450
Seat Post Insertion Depth (mm)	235	260	285
座(立)管角度	76.5°	76.5°	76.5°
上管長度 (mm)	579	606	635
頭管長度 (mm)	100	115	130
頭管角度	64.5°	64.5°	64.5°
前叉 (mm)	44	44	44
Trail (mm)	132	132	132
前後輪距 (mm)	1229	1259	1291
後下叉長度 (mm)	468	468	468
五通下降高度 (mm)	26	26	26
頭碗至五通高度 (mm)	614	628	641
頭碗至五通長度 (mm)	431	455	480
上管至地面高度 (mm)	746	744	756
把手寬 (mm)	780	780	780
龍頭長度 (mm)	40	40	40
曲柄長度 (mm)	165	165	165
輪組尺寸	29"	29"	29"

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。