STANCE E+ 2 625 20MPH



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology, Class 1, Max Assist Speed 20 MPH
CONTROLLER	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
FRAME	
SIZES	S, M, L, XL
COLORS	Black Diamond
FRAME	ALUXX SL-grade aluminum, 1.5"~1.8" head tube,125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
FORK	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
SHOCK	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal single lock-on
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Giant Sport
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano Deore LinkGlide
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore LinkGlide, 10-speed
BRAKES	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Tektro HD-M745 Orion
CASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
CHAIN	Shimano, LinkGlide, CN-LG500
CRANKSET	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

WHEELS	
RIMS	Giant AM30, Tubeless ready, 30mm inner width, 29"
HUBS	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPOKES	Stainless Steel
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 29X2.40" WT Foldable, TLR, EXO, 60TPI [R]
EXTRAS	-
ACCESSORIES	
LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
CARRIER	-

Recommended Retail Price: $4,400.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (inch)	15.7	16.7	17.7	18.7
Seat Tube Angle	76.0°	76.0°	76.0°	76.0°
Top Tube Length (inch)	22.8	23.9	25.2	26.4
Head Tube Length (inch)	4.1	4.5	4.9	5.3
Head Tube Angle	65.5°	65.5°	65.5°	65.5°
Fork Rake (inch)	1.7	1.7	1.7	1.7
Trail (inch)	4.9	4.9	4.9	4.9
Wheelbase (inch)	47.4	48.5	49.9	51.2
Chain Stay Length (inch)	18.4	18.4	18.4	18.4
Bottom Bracket Drop (inch)	1.6	1.6	1.6	1.6
Stack (inch)	24.3	24.7	25	25.4
Reach (inch)	16.7	17.7	18.9	20.1
Stand Over Height (inch)	29.9	29.9	30.7	31.3
Handlebar Width (inch)	30.7	30.7	30.7	30.7
Stem Length (inch)	1.6	1.6	2	2
Crank Length (inch)	6.5	6.5	6.5	6.5
Wheel Size	29"	29"	29"	29"

**All specifications and prices listed are subject to change without notice.*
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.