

STANCE E+ 2 625

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
CONTROLLER	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
DISPLAY	RideControl Dash, full colour LCD screen
BATTERY	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
FRAME	
SIZES	S, M, L, XL
COLOURS	Black Diamond
FRAME	ALUXX SL-grade aluminium, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5-1.8" headset
FORK	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
SHOCK	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser
GRIPS	Giant Tactal single lock-on
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Giant Sport
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano Deore LinkGlide
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore LinkGlide, 10-speed
BRAKES	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Tektro HD-M745 Orion
CASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
CHAIN	Shimano, LinkGlide, CN-LG500
CRANKSET	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM 29"
HUBS	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPOKES	Stainless Steel
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 29X2.40" WT Foldable, TLR, EXO, 60TPI [R]
EXTRAS	-
ACCESSORIES	
LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
CARRIER	-

Price: \$6,299.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	76.0°	76.0°	76.0°	76.0°
Top Tube Length (mm)	580	607	639	671
Head Tube Length (mm)	105	115	125	135
Head Tube Angle	65.5°	65.5°	65.5°	65.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Wheelbase (mm)	1204	1233	1267	1301
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Stand Over Height (mm)	760	760	780	796
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	29"	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.