

STANCE E+ 2 625

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
ACCU	EnergyPak Smart 625, EnergyPak Plus 250Wh range extender compatible
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
FRAME	
MATEN	S, M, L, XL
KLEUREN	Black Diamond
FRAME	ALUXX SL-grade aluminum, 1.5"-1.8" head tube, 125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
VOORVORK	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
DEMPER	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
ONDERDELEN	
STUUR	Giant Connect TR Riser 31.8x780mm
HANDVATTEN	Giant Tactal single lock-on
STUURPEN	Giant Contact
ZADEL	Giant Sport
PEDALEN	Aluminum Platform
AFMONTAGE	
SHIFTERS	Shimano Deore LinkGlide
VOORDERAILLEUR	MRP HD2 co-moulded chain guide
ACHTERDERAILLEUR	Shimano Deore LinkGlide, 10-speed
REMMEN	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
REMHENDELS	Tektro HD-M745 Orion
CASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
AANDRIJVING	Shimano, LinkGlide, CN-LG500
CRANKSET	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant AM30, Tubeless ready, 30mm inner width, 29"
NAVEN	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPAKEN	Stainless Steel
BANDEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F] Maxxis Dissector 29X2.40" WT Foldable, TLR, EXO, 60TPI [R]
EXTRA'S	-
ACCESSOIRES	
VERLICHTING	-
SLOT	Torx 25 Battery Lock with built-in Torque limiter
DRAGER	-

Adviesprijs: € 4.199,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis lengte (mm)	400	425	450	475
Zitbuis hoek	76,0°	76,0°	76,0°	76,0°
Frame Lengte (horizontaal) (mm)	580	607	639	671
Balhoofdbuis Lengte (mm)	105	115	125	135
Balhoofdbuis Hoek	65,5°	65,5°	65,5°	65,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	124	124	124	124
Wielbasis (mm)	1204	1233	1267	1301
Liggende achtervork lengte (mm)	468	468	468	468
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Stand Over Height (mm)	760	760	780	796
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	40	40	50	50
Cranklengte (mm)	165	165	165	165
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.