

STANCE E+ 2

GIANT



SPECS

| HYBRID CYCLING TECHNOLOGY |                                                                                                                                                                                                               |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MOTOR                     | Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology                                                                                                                                                    |
| CONTROLLER                | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels                                                                                                                                       |
| DISPLAY                   | Giant RideControl Dash 2, full color LCD display                                                                                                                                                              |
| BATTERY                   | Giant EnergyPak 625Wh                                                                                                                                                                                         |
| CHARGER                   | Giant EnergyPak 4A smart charger                                                                                                                                                                              |
| FRAME                     |                                                                                                                                                                                                               |
| SIZES                     | S, M, L, XL                                                                                                                                                                                                   |
| FRAME                     | ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (ZS62/ZS72) |
| FORK                      | Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible                                                     |
| SHOCK                     | Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)                                                                                                         |
| COMPONENTS                |                                                                                                                                                                                                               |
| HANDLEBAR                 | Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]                                                                                                                                                  |
| GRIPS                     | Giant Tactal Pro single lock-on                                                                                                                                                                               |
| STEM                      | Giant Contact SL 35                                                                                                                                                                                           |
| SEATPOST                  | Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170m, L/XL: 170~200mm)                                                                                                             |
| SADDLE                    | Giant Contact Ergo Trail                                                                                                                                                                                      |
| PEDALS                    | Large platform pedal, 28-pins, PP cage, Steel axle                                                                                                                                                            |
| DRIVETRAIN                |                                                                                                                                                                                                               |
| SHIFTERS                  | Shimano Cues LinkGlide                                                                                                                                                                                        |
| REAR DERAILLEUR           | Shimano Cues LinkGlide, 10-speed, Shadow+                                                                                                                                                                     |
| BRAKES                    | Tektro Orion, hydraulic disc, 4-piston, 203mm [F/R]                                                                                                                                                           |
| BRAKE LEVERS              | Tektro Orion                                                                                                                                                                                                  |
| CASSETTE                  | Shimano Cues LinkGlide, 10-speed, 11-48T                                                                                                                                                                      |
| CHAIN                     | Shimano LinkGlide                                                                                                                                                                                             |
| CRANKSET                  | Forged aluminum crank arms                                                                                                                                                                                    |

| WHEELS             |                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------|
| RIMS               | Giant AM30, Tubeless ready, 30mm inner width                                                            |
| HUBS               | Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]                                             |
| SPOKES             | Stainless Steel                                                                                         |
| TIRES              | Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40"" WT Foldable TLR EXO [R] |
| ACCESSORIES        |                                                                                                         |
| LOCK               | Torx 25 Battery Lock with built-in Torque limiter                                                       |
| FENDER/CHAINGUARD  | MRP 1x HD guide, CS e-Mount, 32~38T Adjustable                                                          |
| LIMITS             |                                                                                                         |
| MAX CHAINRING SIZE | Direct-mount steel 36T (maximum: 38T)                                                                   |

GEOMETRY

| FRAME                          | S     | M     | L     | XL    |
|--------------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)          | 400   | 425   | 450   | 475   |
| Seat Post Insertion Depth (mm) | 235   | 260   | 285   | 310   |
| Seat Tube Angle                | 76,5° | 76,5° | 76,5° | 76,5° |
| Top Tube Length (mm)           | 579   | 606   | 635   | 663   |
| Head Tube Length (mm)          | 100   | 115   | 130   | 145   |
| Head Tube Angle                | 64,5° | 64,5° | 64,5° | 64,5° |
| Fork Rake (mm)                 | 44    | 44    | 44    | 44    |
| Trail (mm)                     | 132   | 132   | 132   | 132   |
| Wheelbase (mm)                 | 1229  | 1259  | 1291  | 1322  |
| Chain Stay Length (mm)         | 468   | 468   | 468   | 468   |
| Bottom Bracket Drop (mm)       | 26    | 26    | 26    | 26    |
| Stack (mm)                     | 614   | 628   | 641   | 655   |
| Reach (mm)                     | 431   | 455   | 480   | 505   |
| Stand Over Height (mm)         | 746   | 744   | 756   | 762   |
| Handlebar Width (mm)           | 780   | 780   | 780   | 780   |
| Stem Length (mm)               | 40    | 40    | 40    | 40    |
| Crank Length (mm)              | 165   | 165   | 165   | 165   |
| Wheel Size                     | 29"   | 29"   | 29"   | 29"   |

All specifications listed are subject to change without notice.