

STANCE E+ 2

GIANT



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
ECRÃ	Giant RideControl Dash 2, full color LCD display
BATERIA	Giant EnergyPak 625Wh
CARREGADOR	Giant EnergyPak 4A smart charger
QUADRO	
TAMANHOS	S, M, L, XL
QUADRO	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5-1.8" headset (ZS62/ZS72)
FORQUILHA	Giant STL 36 Air, 150mm travel, 5-position compression adjust, tapered steerer, 72mm crown, e-bike optimized, 110x15mm Boost axle, full fender compatible
AMORTECEDORES	Giant Crest FloTrac, 3-position lever, e-bike optimized, 185x52.5mm Sag recommendation: 30% (15.75mm)
COMPONENTES	
GUIADOR	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
PUNHOS	Giant Tactal Pro single lock-on
AVANÇO	Giant Contact SL 35
ESPIGÃO DE SELIM	Giant Contact Switch AT travel adjust dropper seatpost (S:110-140mm, M:140-170mm, L/XL: 170-200mm)
SELIM	Giant Contact Ergo Trail
PEDAIS	Large platform pedal, 28-pins, PP cage, Steel axle
TRANSMISSÃO	
MANETES	Shimano Cues LinkGlide
DESVIADOR TRASEIRO	Shimano Cues LinkGlide, 10-speed, Shadow+
TRAVÕES	Tektro Orion, hydraulic disc, 4-piston, 203mm [F/R]
MANÍPULOS DOS TRAVÕES	Tektro Orion
CASSETTE	Shimano Cues LinkGlide, 10-speed, 11-48T
CORRENTE	Shimano LinkGlide
CONJUNTO PEDALEIRO	Forged aluminum crank arms

RODAS	
AROS	Giant AM30, Tubeless ready, 30mm inner width
CUBOS	Shimano TC500 Boost, Center-Lock, 15x110mm [F] 12x148mm [R]
RAIOS	Stainless Steel
PNEUS	Maxxis Minion DHF 29X2.50" WT Foldable, TLR, EXO [F] Maxxis Dissector 29X2.40" WT Foldable TLR EXO [R]
ACESSÓRIOS	
CADEADO	Torx 25 Battery Lock with built-in Torque limiter
GUARDA LAMAS/PROTECTOR DE CORRENTE	MRP 1x HD guide, CS e-Mount, 32-38T Adjustable
LIMITES	
TAMANHO MÁXIMO DA COROA	Direct-mount steel 36T (maximum: 38T)

Preço: 3 499,00 €

GEOMETRIA

QUADRO	S	M	L	XL
Comprimento do tubo do assento (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Ângulo do tubo do assento	76,5°	76,5°	76,5°	76,5°
Comprimento do tubo superior (mm)	579	606	635	663
Comprimento do tubo principal (mm)	100	115	130	145
Ângulo do tubo principal	64,5°	64,5°	64,5°	64,5°
Garfo acincho (mm)	44	44	44	44
Trilha (mm)	132	132	132	132
distância entre eixos (mm)	1229	1259	1291	1322
Comprimento Chain Stay (mm)	468	468	468	468
Suporte inferior (mm)	26	26	26	26
Pilha (mm)	614	628	641	655
Alcançar (mm)	431	455	480	505
Altura do standover (mm)	746	744	756	762
Largura do guidão (mm)	780	780	780	780
Comprimento da haste (mm)	40	40	50	50
Comprimento da Manivela (mm)	165	165	165	165
Tamanho da roda	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.