



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	T/K
FRAME	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
FORK	Giant STL 34 dual air, 140mm, 15x110, thru-axle
SHOCK	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
GRIPS	Giant Tactal, lock on
STEM	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
SEATPOST	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Contact Ergo Trail
DRIVETRAIN	
SHIFTERS	Shimano CUES SL-6000, 1x10
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano CUES RD-U6000, Shadow +
BRAKES	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
BRAKE LEVERS	Tektro HD-M5141
CASSETTE	Shimano CUES, CS-LG300, 11x48
CHAIN	KMC X-11
CRANKSET	Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	Shimano, threaded

WHEELS	
RIMS	Giant AM30 alloy rim
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
SPOKES	stainless, 28, J-bend
TIRES	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

Suggested Retail Price (CDN): \$2,599.00

FRAME GEOMETRY

FRAME	XS	S	M	L	XL
Seat Tube Length (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Seat Tube Angle	77.0°	76.5°	76.5°	76.5°	76.5°
Top Tube Length (mm)	548.1	568	602	628	661
Head Tube Length (mm)	90	95	100	115	120
Head Tube Angle	65.0°	65.0°	65.0°	65.0°	65.0°
Fork Rake (mm)	44	44	44	44	44
Trail (mm)	129	129	129	129	129
Wheelbase (mm)	1158.1	1176	1210	1239	1274
Chain Stay Length (mm)	440	442	442	442	442
Bottom Bracket Drop (mm)	25	40	40	40	40
Stack (mm)	608.7	610	615	628	633
Reach (mm)	407.4	422	454	477	509
Stand Over Height (mm)	757	747	747	747	747
Handlebar Width (mm)	760	760	760	780	780
Stem Length (mm)	40	40	40	40	40
Crank Length (mm)	165	165	165	165	165
Wheel Size	29" [F] 27.5" [R]	29"	29"	29"	29"

All prices and specifications are subject to change without notice.