# STANCE

## ESPECIFICACIONES

| CUADRO | |
|---|---|
| **TALLAS** | S, M, L, XL |
| **COLORES** | T/K |
| **CUADRO** | ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution |
| **HORQUILLA** | Giant STL 34 dual air, 140mm, 15x110, thru-axle |
| **AMORTIGUADOR** | GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5 |
| **COMPONENTES** | |
| **MANILLAR** | Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm ride/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm |
| **PUÑOS** | Giant Tactal, lock on |
| **POTENCIA** | Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm |
| **TIJA DE SILLÍN** | Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm |
| **SILLÍN** | Giant Contact Ergo Trail |
| **TRANSMISIÓN** | |
| **MANETAS DE CAMBIO** | Shimano CUES SL-6000, 1x10 |
| **DESVIADOR** | N/A |
| **CAMBIO TRASERO** | Shimano CUES RD-U6000, Shadow + |
| **FRENOS** | Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm |
| **PALANCAS DE FRENOS** | Tektro HD-M5141 |
| **CASETTE** | Shimano CUES, CS-LG300, 11x48 |
| **CADENA** | KMC X-11 |
| **JGO. PLATOS Y BIELAS** | Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm |
| **CAJA DE PEDALIER** | Shimano, threaded |

| RUEDAS | |
|---|---|
| **LLANTAS** | Giant AM30 alloy rim |
| **BUJES** | [F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body |
| **RADIOS** | stainless, 28, J-bend |
| **CUBIERTAS** | [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless |
| **EXTRAS** | tubeless prepared, max tire size 2.5", max chainring size 32t |

**Precio: 1.999,00 €**

## GEOMETRÍA

| CUADRO | XS | S | M | L | XL |
|---|---|---|---|---|---|
| Longitud del tubo del sillín (mm) | 380 | 400 | 425 | 450 | 475 |
| Seat Post Insertion Depth (mm) | 250 | 270 | 290 | 320 | 390 |
| Ángulo del tubo del sillín | 77,0° | 76,5° | 76,5° | 76,5° | 76,5° |
| Longitud del tubo superior (mm) (mm) | 547 | 567 | 600 | 627 | 659 |
| Longitud del tubo de dirección (mm) (mm) | 95 | 100 | 110 | 120 | 130 |
| Ángulo del tubo de dirección | 65,0° | 65,0° | 65,0° | 65,0° | 65,0° |
| Inclinación de la horquilla (mm) | 44 | 44 | 44 | 44 | 44 |
| Trail (mm) (mm) | 129 | 129 | 129 | 129 | 129 |
| Distancia entre ejes (mm) (mm) | 1158 | 1176 | 1210 | 1239 | 1274 |
| Longitud de la vaina (mm) (mm) | 440 | 442 | 442 | 442 | 442 |
| Caída del eje de pedalier (mm) (mm) | 25 | 40 | 40 | 40 | 40 |
| Stack (mm) (mm) | 613 | 615 | 624 | 633 | 642 |
| Reach (mm) (mm) | 405 | 420 | 450 | 475 | 505 |
| Altura del suelo al tubo (mm) (mm) | 758 | 754 | 748 | 744 | 738 |
| Ancho del manillar (mm) (mm) | 760 | 760 | 760 | 780 | 780 |
| Longitud de la potencia (mm) (mm) | 40 | 40 | 40 | 40 | 40 |
| Longitud de las bielas (mm) (mm) | 165 | 165 | 165 | 165 | 165 |
| Tamaño de ruedas | 29" [F] 27.5" [R] | 29" | 29" | 29" | 29" |

*Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.*