



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	T/K
CUADRO	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
TIJERA	Giant STL 34 dual air, 140mm, 15x110, thru-axle
AMORTIGUADOR	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
COMPONENTES	
MANUBRIO	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
GRIPS	Giant Tactal, lock on
POTENCIA	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
POSTE DE ASIENTO	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
ASIENTO	Giant Contact Ergo Trail
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano CUES SL-6000, 1x10
DESVIADOR	N/A
CAMBIO TRASERO	Shimano CUES RD-U6000, Shadow +
FRENOS	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
PALANCAS DE FRENOS	Tektro HD-M5141
CASSETTE	Shimano CUES, CS-LG300, 11x48
CADENA	KMC X-11
MULTIPLICACIÓN	Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
EJE DE CENTRO	Shimano, threaded

RUEDAS	
RUEDAS	Giant AM30 alloy rim
MAZAS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
RAYOS	stainless, 28, J-bend
NEUMÁTICOS	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

Precio: \$54,990.00

GEOMETRÍA

CUADRO	XS	S	M	L	XL
Longitud de la Base del Poste de Asiento (mm)	380	400	425	450	475
Seat Post Insertion Depth (mm)	250	270	290	320	390
Ángulo de la Base del Poste de Asiento	77.0°	76.5°	76.5°	76.5°	76.5°
Longitud del Tubo Superior (mm)	547	567	600	627	659
Longitud del Telescopio (mm)	95	100	110	120	130
Ángulo del Telescopio	65.0°	65.0°	65.0°	65.0°	65.0°
Rake (mm)	44	44	44	44	44
Trail (mm)	129	129	129	129	129
Distancia entre Ejes (mm)	1158	1176	1210	1239	1274
Longitud de Vaina Inferior (mm)	440	442	442	442	442
Caída del Eje de Centro (mm)	25	40	40	40	40
Stack (mm)	613	615	624	633	642
Reach (mm)	405	420	450	475	505
Altura del Tubo Superior al Suelo (mm)	758	754	748	744	738
Ancho del Manubrio (mm)	760	760	760	780	780
Longitud de la Potencia (mm)	40	40	40	40	40
Longitud de la Biela (mm)	165	165	165	165	165
Tamaño de las Ruedas	29" [F] 27.5" [R]	29"	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.