

STANCE



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Black
TELAIO	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
FORCELLA	Giant STL 34 dual air, 140mm, 15x110, thru-axle
AMMORTIZZATORE	Crest FloTrac Elite TR, 2-position lockout, 210x52.5
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
MANOPOLE	Giant Tactal, lock on
ATTACCO MANUBRIO	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
REGGISSELLA	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Contact Ergo Trail
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano CUES SL-6000, 1x10
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano CUES RD-U6000, Shadow +
FRENI	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
COMANDI FRENO	Tektro HD-M5141
PACCO PIGNONI	Shimano CUES, CS-LG300, 11x48
CATENA	KMC X-11
GUARNITURA	Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
MOVIMENTO CENTRALE	Shimano, threaded

RUOTE	
CERCHI	Giant AM30 alloy rim
MOZZI	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
RAGGI	stainless, 28, J-bend
COPERTONI	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
EXTRA	tubeless prepared, max tire size 2.5", max chainring size 32t

Prezzo: 2.199,00 €

GEOMETRIA

TELAIO	XS	S	M	L	XL
Lunghezza Tubo Sella (mm)	380	400	425	450	475
Profondità inserimento reggisella (mm)	250	270	290	320	390
Angolo Tubo Sella	77,0°	76,5°	76,5°	76,5°	76,5°
Lunghezza Tubo Orizzontale (mm)	547	567	600	627	659
Lunghezza Tubo Sterzo (mm)	95	100	110	120	130
Angolo Sterzo	65,0°	65,0°	65,0°	65,0°	65,0°
Rake Forcella (mm)	44	44	44	44	44
Avancorsa (mm)	129	129	129	129	129
Interasse (mm)	1158	1176	1210	1239	1274
Lunghezza Carro Posteriore (mm)	440	442	442	442	442
Drop Movimento Centrale (mm)	25	40	40	40	40
Stack (mm)	613	615	624	633	642
Reach (mm)	405	420	450	475	505
Altezza stand over (mm)	758	754	748	744	738
Larghezza Manubrio c/c (mm)	760	760	760	780	780
Lunghezza Attacco Manubrio (mm)	40	40	40	40	40
Lunghezza Pedivella (mm)	165	165	165	165	165
Dimensione Ruote	29" [F] 27.5" [R]	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.