



## SPECIFICATIES

| FRAME            |  |
|------------------|--|
| MATEN            | S, M, L, XL  |
| KLEUREN          | Black, Almond  |
| FRAME            | ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution   |
| VOORVORK         | Giant STL 34 dual air, 140mm, 15x110, thru-axle  |
| DEMPER           | Crest FloTrac Elite TR, 2-position lockout, 210x52.5   |
| ONDERDELEN       |  |
| STUUR            | Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm   |
| HANDVATTEN       | Giant Tactal, lock on  |
| STUURPEN         | Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm  |
| ZADELPEN         | Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm |
| ZADEL            | Giant Contact Ergo Trail   |
| AFMONTAGE        |  |
| SHIFTERS         | Shimano CUES SL-6000, 1x10   |
| VOORDERAILLEUR   | N/A  |
| ACHTERDERAILLEUR | Shimano CUES RD-U6000, Shadow +  |
| REMMEN           | Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm  |
| REMHENDELS       | Tektro HD-M5141  |
| CASSETTE         | Shimano CUES, CS-LG300, 11x48  |
| AANDRIJVING      | KMC X-11   |
| CRANKSET         | Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm  |
| BOTTOM BRACKET   | Shimano, threaded  |

| WIELSET |   |
|---------|---|
| VELGEN  | Giant AM30 alloy rim  |
| NAVEN   | [F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body                         |
| SPAKEN  | stainless, 28, J-bend   |
| BANDEN  | [F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless |
| EXTRA'S | tubeless prepared, max tire size 2.5", max chainring size 32t                                   |

Adviesprijs: € 2.199,00

## GEOMETRIE

| FRAME                           | S     | M     | L     | XL    |
|---------------------------------|-------|-------|-------|-------|
| Zitbuis Lengte (mm)             | 400   | 425   | 450   | 475   |
| Seat Post Insertion Depth (mm)  | 270   | 290   | 320   | 390   |
| Zitbuis Hoek                    | 76,5° | 76,5° | 76,5° | 76,5° |
| Frame Lengte (horizontaal) (mm) | 568   | 602   | 628   | 661   |
| Balhoofdbuis Lengte (mm)        | 95    | 100   | 115   | 120   |
| Balhoofdbuis Hoek               | 65,0° | 65,0° | 65,0° | 65,0° |
| Vork Sprong (mm)                | 44    | 44    | 44    | 44    |
| Naloop (mm)                     | 129   | 129   | 129   | 129   |
| Wielbasis (mm)                  | 1176  | 1210  | 1239  | 1274  |
| Liggende achtervork lengte (mm) | 442   | 442   | 442   | 442   |
| Bottom Bracket Drop (mm)        | 40    | 40    | 40    | 40    |
| Stack (mm)                      | 610   | 615   | 628   | 633   |
| Reach (mm)                      | 422   | 454   | 477   | 509   |
| Stand Over Height (mm)          | 747   | 747   | 747   | 747   |
| Stuur breedte (mm)              | 760   | 760   | 780   | 780   |
| Stuurpen Lengte (mm)            | 40    | 40    | 40    | 40    |
| Cranklengte (mm)                | 165   | 165   | 165   | 165   |
| Wielmaat                        | 29"   | 29"   | 29"   | 29"   |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.