

STANCE



產品規格

車架	
尺寸	S, M, L
顏色	黑
車架	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
前叉	Giant STL 34 dual air, 140mm, 15x110, thru-axle
避震器	Crest FloTrac Elite TR, 2-position lockout, 210x52.5
COMPONENTS	
車把手	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm,
把手帶/套	Giant Tactal, lock on
豎桿	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm
座桿	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm
坐墊	Giant Contact Ergo Trail
DRIVETRAIN	
變速把手	Shimano CUES SL-6000, 1x10
前變速器	N/A
後變速器	Shimano CUES RD-U6000, Shadow +
煞車系統	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
煞車把手	Tektro HD-M5141
飛輪	Shimano CUES, CS-LG300, 11x48
鏈條	KMC X-11
大齒盤	Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET (B B)	Shimano, threaded

輪組	
輪圈	Giant AM30 alloy rim
花鼓	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
輻條	stainless, 28, J-bend
外胎	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
其他	tubeless prepared, max tire size 2.5", max chainring size 32t

Price: NT\$62,800

車架幾何

車架	S	M	L
座(立)管長 (mm)	400	425	450
Seat Post Insertion Depth (mm)	270	290	320
座(立)管角度	76.5°	76.5°	76.5°
上管長度 (mm)	567	600	627
頭管長度 (mm)	100	110	120
頭管角度	65.0°	65.0°	65.0°
前叉 (mm)	44	44	44
Trail (mm)	129	129	129
前後輪距 (mm)	1176	1210	1239
後下叉長度 (mm)	442	442	442
五通下降高度 (mm)	40	40	40
頭碗至五通高度 (mm)	615	624	633
頭碗至五通長度 (mm)	420	450	475
上管至地面高度 (mm)	754	748	744
把手寬 (mm)	760	760	780
龍頭長度 (mm)	40	40	40
曲柄長度 (mm)	165	165	165
輪組尺寸	29"	29"	29"

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。