



SPEZIFIKATIONEN

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|---|
| MOTOR | Giant SyncDrive Pro2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology |
| SENSOR | Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 manual support levels, USB-C (10W) |
| DISPLAY | Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation Giant RideDash EVO, high-angle visibility, 3" full color LCD |
| AKKU | Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production |
| CHARGER | Giant EnergyPak 6A smart charger, 60% in 3:00h |
| CONNECTIVITY | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| RAHMEN | |
| GRÖSSEN | S, M, L, XL |
| FARBE | Hematite |
| RAHMEN | ALUXX SL aluminum, 100mm Stable Link Suspension System, Overdrive 3, 1.8" - 1.5" head tube, w/ Integrated KSA18 kickstand mount, Giant EnergyPak Plus range extender included |
| GABEL | Fox AWL 1.5" tapered steerer, 100mm travel, RAIL damper, Boost 110x15QR, ESUV-optimized |
| DÄMPFER | Fox Float DPS, 165x38mm, trunnion, custom tuned |
| KOMPONENTEN | |
| LENKER | Giant Contour Comfort Riser 31.8x720mm |
| GRIFFE | Giant Connect Ego Max Plus |
| VORBAU | Giant Contour EVO display integrated stem (S/M: 80mm, L/XL: 100mm) |
| SATTELSTÜTZE | Giant Contact Switch, dropper, 30,9mm (S:100mm/ M:125mm/ L:150mm/ XL:170mm) |
| SATTEL | Selle Royal Vivo Ergo GTS |
| PEDALE | Aluminum Platform |
| ANTRIEB | |
| SCHALTHEBEL | Enviolo Automatiq Pure Controller |
| UMWERFER | - |
| SCHALTWERK | - |
| BREMSEN | Shimano Deore BR-M6120, 4-piston, hydraulic disc, 203mm |
| BREMSHEBEL | Shimano Deore |
| KASSETTE | Gates 24T |
| KETTE | Gates CDX carbon 130T |
| KURBEL | Gates CDX 46T Praxis e-Cadet crankarm set |
| TRETLAGER | N/A |

| LAUFRÄDER | |
|---------------------|--|
| FELGEN | Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized |
| NABE | Giant eTracker Boost, 6-bolt, 110x15 e-bike optimized [F] Enviolo Heavy Duty autoshift [R] |
| SPEICHEN | Sapim Strong [R] Race [F], e-bike optimized |
| REIFEN | Maxxis Rekon 27.5x2.6", 60TPI Foldable TLR EXO |
| EXTRAS | KSA18 direct mount kickstand, Tubeless kit (liquid, valves, levers, manual, tool) |
| ACCESSORIES | |
| BELEUCHTUNG | Supernova M99 Mini Pro front LED Supernova E3 Tail Light - fender integrated |
| SCHLOSS | ABUS Xplus battery lock |
| GEPÄCKTRÄGER | Suspended carrier system rear. MIK system |

GEOMETRIEDATEN

| RAHMEN | S | M | L | XL |
|--------------------------|-------|-------|-------|-------|
| Sitzrohrlänge (mm) | 445 | 445 | 460 | 490 |
| Sitzrohrwinkel | 73.5° | 73.5° | 73.5° | 73.5° |
| Oberrohrlänge (mm) | 580 | 595 | 610 | 630 |
| Steuerrohr-Länge (mm) | 125 | 140 | 155 | 170 |
| Steuerrohr-Winkel | 69.0° | 69.5° | 69.5° | 69.5° |
| Gabelneigung (mm) | 51 | 51 | 51 | 51 |
| Trail (mm) | 82 | 82 | 82 | 82 |
| Radstand (mm) | 1152 | 1169 | 1185 | 1206 |
| Kettenstreben-Länge (mm) | 480 | 480 | 480 | 480 |
| Tretlager-Höhe (mm) | 40 | 40 | 40 | 40 |
| Stack (mm) | 623 | 637 | 651 | 665 |
| Reach (mm) | 395 | 406 | 417 | 433 |
| Lenkerbreite (mm) | 720 | 720 | 720 | 720 |
| Vorbaulänge (mm) | 80 | 80 | 100 | 100 |
| Kurbellänge (mm) | 165 | 165 | 165 | 170 |
| Radgrösse | 27.5" | 27.5" | 27.5" | 27.5" |

Spezifikations-, Preis- und Farbänderungen vorbehalten.