

# STORMGUARD E+ 1

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Pro2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
<b>SENSOR</b>	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 manual support levels, USB-C (10W)
<b>DISPLAY</b>	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation Giant RideDash EVO, high-angle visibility, 3" full color LCD
<b>BATTERY</b>	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
<b>CHARGER</b>	Giant EnergyPak 6A smart charger, 60% in 3:00h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
<b>MARIMI</b>	S, M, L, XL
<b>CULORI</b>	Hematite
<b>CADRU</b>	ALUXX SL aluminum, 100mm Stable Link Suspension System, Overdrive 3, 1.8" - 1.5" head tube, w/ Integrated KSA18 kickstand mount, Giant EnergyPak Plus range extender included
<b>FURCA</b>	Fox AWL, 1.5" tapered steerer, 100mm travel, RAIL damper, Boost 110x15QR, ESUV-optimized
<b>SOC</b>	Fox Float DPS, 165x38mm, trunnion, custom tuned
COMPONENTE	
<b>GHIDON</b>	Giant Contour Comfort Riser 31.8x720mm
<b>GRIPS</b>	Giant Connect Ego Max Plus
<b>PIPA</b>	Giant Contour EVO display integrated stem (S/M: 80mm, L/XL: 100mm)
<b>TIJA SA</b>	Giant Contact Switch, dropper, 30,9mm (S:100m/ M:125mm/ L:150mm/ XL:170mm)
<b>SA</b>	Selle Royal Vivo Ergo GTS
<b>PEDALE</b>	Aluminum Platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
<b>MANETE SCHIMBATOR</b>	Enviolo Automatiq Pure Controller
<b>SCHIMBATOR FATA</b>	-
<b>SCHIMBATOR SPATE</b>	-
<b>FRANE</b>	Shimano Deore BR-M6120, 4-piston, hydraulic disc, 203mm
<b>MANETE FRANA</b>	Shimano Deore
<b>PINIOANE</b>	Gates 24T
<b>LANT</b>	Gates CDX carbon 130T
<b>ANGRENAJ</b>	Gates CDX 46T Praxis e-Cadet crankarm set
<b>BOTTOM BRACKET</b>	N/A

ROTI	
<b>JANTE</b>	Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized
<b>BUTUCI</b>	Giant eTracker Boost, 6-bolt, 110x15 e-bike optimized [F] Enviolo Heavy Duty autoshift [R]
<b>SPITE</b>	Sapim Strong [R] Race [F], e-bike optimized
<b>ANVELOPE</b>	Maxxis Rekon 27.5x2.6", 60TPI Foldable TLR EXO
<b>EXTRAS</b>	KSA18 direct mount kickstand, Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
<b>LIGHTING</b>	Supernova M99 Mini Pro front LED Supernova E3 Tail Light - fender integrated
<b>LOCK</b>	ABUS Xplus battery lock
<b>CARRIER</b>	Suspended carrier system rear. MIK system

## GEOMETRIE

CADRU	S	M	L	XL
Seat Tube Length (mm)	445	445	460	490
Seat Tube Angle	73,5°	73,5°	73,5°	73,5°
Top Tube Length (mm)	580	595	610	630
Head Tube Length (mm)	125	140	155	170
Head Tube Angle	69,0°	69,5°	69,5°	69,5°
Fork Rake (mm)	51	51	51	51
Trail (mm)	82	82	82	82
Wheelbase (mm)	1152	1169	1185	1206
Chain Stay Length (mm)	480	480	480	480
Bottom Bracket Drop (mm)	40	40	40	40
Stack (mm)	623	637	651	665
Reach (mm)	395	406	417	433
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	80	80	100	100
Crank Length (mm)	165	165	165	170
Wheel Size	27.5"	27.5"	27.5"	27.5"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.