



TECHNIQUES

CADRE	
TAILLES	OSFM
COLORIS	Quicksilver
CADRE	ALUXX-grade aluminum, 10x135mm horizontal sliding dropouts
FOURCHE	Marzocchi Bomber DJ, 36mm stanchions, GRIP damper, 20x110mm non-boost, 100mm travel, 1.5 tapered steerer, compression and rebound adjustment
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact TR35, alloy, 760mm, 35mm rise
POIGNÉES	Giant Tactal Pro, lock on
POTENCE	Giant Contact 35 DJ, 0-degree, 35mm
TIGE DE SELLE	alloy, two-bolt, 30.9x300mm
SELLE	Giant Ergo Contact Trail
DÉRAILLEUR	
MANETTES	N/A
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	N/A
FREINS	[R] Shimano MT500, hydraulic TR-55 ; [F] mechanical disc (in small box)
LEVIER DE FREIN	Shimano BL-MT501
CASSETTE	13t, stainless steel
CHAÎNE	KMC Z1 wide
PÉDALIER	Prowheel forged, alloy, 30t, 165mm
BOITIER DE PÉDALIER	73mm, threaded

ROUES	
JANTES	Giant TRA 2 with Wideguard technology, 26", alloy
MOYEURS	Giant Disc, 32h, [F] 20x110 [R] 10x135 thru-axle, alloy, disc
RAYONS	stainless, 14g
PNEUS	Kenda Booster, 26x2.25"
EXTRAS	Mechanical disc for front wheel (in small box)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 1 500,00 €

GÉOMÉTRIE

CADRE	One Size
Longueur de tube de selle (mm)	310
Seat Post Insertion Depth (mm)	225
Angle de tube de selle	72,0°
Longueur du tube supérieur (mm)	594
Longueur du tube de direction (mm)	120
Angle du tube de direction	68,5°
Déport de fourche (mm)	37
Trail (mm)	95
Empattement (mm)	1047
Longueur des bases (mm)	385
Drop du boîtier de pédalier (mm)	25
Stack (mm)	566
Reach (mm)	410
Hauteur en statique (mm)	672
Largeur de cintre (mm)	760
Longueur de potence (mm)	35
Longueur des manivelles (mm)	165

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.