

STP 26



SPECS

RAMME	
STØRRELSE	OSFM
FARGE	Quicksilver
RAMME	ALUXX-grade aluminum, 10x135mm horizontal sliding dropouts
GAFFEL	Marzocchi Bomber DJ, 36mm stanchions, GRIP damper, 20x110mm, 100mm travel
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact TR35, alloy, 760mm, 35mm rise
GRIPS	Giant Tactal Pro, lock on
STYRSTEM	Giant Contact 35 DJ, 0-degree, 35mm
SETEPINNE	alloy, two-bolt, 30.9x300mm
SADEL	Giant Ergo Contact Trail
DRIVVERK	
GIRHENDLER	N/A
FRONTGIR	N/A
BAKGIR	N/A
BREMSE	[F] mechanical disc, [R] Shimano MT500, hydraulic TR-55 [F]180mm, [R]160mm rotors
BREMSEHENDLER	Shimano BL-MT501
KASSETT	13t, stainless steel
KJEDE	KMC Z1 wide
KRANK	Prowheel forged, alloy, 30t, 165mm
BOTTOM BRACKET	73mm, threaded

HJUL	
FELG	Giant TRA 2, 26", alloy
NAV	Giant Disc, 32h, [F] 20x110 [R] 10x135 thru-axle, alloy, disc
EIKE	stainless, 14g
DEKK	Kenda Booster, 26x2.25"

GEOMETRI

RAMME	One Size
Seat Tube Length (mm)	310
Seat Post Insertion Depth (mm)	225
Seat Tube Angle	72,0°
Top Tube Length (mm)	594
Head Tube Length (mm)	120
Head Tube Angle	68,5°
Fork Rake (mm)	37
Trail (mm)	95
Wheelbase (mm)	1047
Chain Stay Length (mm)	385
Bottom Bracket Drop (mm)	25
Stack (mm)	566
Reach (mm)	410
Stand Over Height (mm)	672
Handlebar Width (mm)	760
Stem Length (mm)	35
Crank Length (mm)	165

Alle spesifikasjonene kan endres uten varsel.