

레인 SX



스펙

프레임	
사이즈	M, L
색상	Sea Sparkle/Hematite
프레임	ALUXX SL-grade aluminum front and rear triangles, 165mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
포크	Fox 40 Performance, GRIP damper, 190mm, 20x110, custom tuned for Giant
서스펜션	Fox DHX2 Performance Elite, lockout, 205/65, custom tuned for Giant M:400#, L:450#
부품	
핸들바	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm
스템	TruVativ Descendant Direct Mount 35, 50mm
시트포스트	Giant Contact, 30.9mm, 400mm
안장	Giant Romero
페달	N/A
구동계	
변속기	Shimano CUES, SL-6000, 1x10
앞 변속기	N/A
뒷 변속기	Shimano CUES RD-U6000
브레이크	SRAM Code R, hydraulic, CenterLine rotors [F]220mm, [R]200mm
브레이크 레버	SRAM Code R
스프라켓	Shimano CUES, CS-LG300, 11-48
체인	Shimano CUES LG500
크랭크 셋	Praxis Cadet HD M24, 32t, 165mm, 55mm chainline
BB	Praxis, press fit

바퀴	
휠	Giant AM 29, alloy
허브	Giant Boost, sealed
스포크	Stainless steel
타이어	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.5 WT, 3C MaxxTerra, DD, TR tubeless
추가 기능	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide

가격: ₩5,550,000

지오메트리

프레임	M	L
	MID HIGH	MID HIGH
시트 튜브 길이 (mm)	425	450
Seat Post Insertion Depth (mm)	383	308
시트 튜브 각도	77.9° 78.3°	77.0° 77.3°
탑튜브 길이 (mm)	588 587	621 620
헤드 튜브 길이 (mm)	105	115
헤드 튜브 각도	63.1° 63.5°	63.1° 63.5°
포크 레이크 (mm)	56	56
트레일 (mm)	129.8 127	130 127
휠베이스 (mm)	1228 1227	1283 1282
체인스테이 길이 (mm)	443 442	443 442
BB (mm)	25 19	25 19
스택 (mm)	635 632	644 641
범위 (mm)	452 456	472 476
스탠드 오버 (mm)	737 742	750 755
핸들바 폭 (mm)	800	800
스템 길이 (mm)	50	50
크랭크 길이 (mm)	165	165
휠사이즈	F 29 R 27.5	F 29 R 27.5

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.